


SLAG/MHW
Apt Elev **3671'**
S19 49.4 W063 57.8

28 JUL 17 **(10-9)**

MONTEAGUDO, BOLIVIA
APIAGUAIKI TUMPA



ADDITIONAL RUNWAY INFORMATION					
RWY		USABLE LENGTHS		TAKE-OFF	WIDTH
		Threshold	Landing Beyond Glide Slope		
16					98'
34					30m
TAKE-OFF					
	All Rwy's				
1 & 2 Eng	1600m				
3 & 4 Eng	800m				

CHANGES: Take-off minimums, runway length, runway material, airport coordinates.

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

SLAG/MHW

APIAGUAIKI TUMPA

2 JUN 17

(12-1)

MISSED APCH CLIMB
GRADIENT MIM 4.5%

CAT A, B & C

MONTEAGUDO, BOLIVIA

RNAV (GNSS) Z Rwy 34

MONTEAGUDO Control

128.2

*MONTEAGUDO Tower

118.3

RNAV

Final

Apch Crs

340°

Minimum Alt

AG767

5500' (1873')

LNAV

MDA(H)

4430' (803')

Apt Elev 3671'

Rwy 3627'

MISSED APCH: Climbing RIGHT turn to 8500' to AG766, enter hold 192° left turns, continue climb to 9000' and request ATC instructions.

MISSED APCH: Distance to AG766

Distance	3.0	6.0	9.0	12.0	15.0
Alt/4.5% Climb Gradient	5300'	6100'	6900'	7700'	8500'

Alt Set: hPa


Rwy Elev: 126 hPa

Trans level: By ATC


Trans alt: 10000'

1. GNSS required. 2. MAX 160 KT.

MSA ARP



DIST to THR	3.0	4.0	5.0
ALTITUDE	4750'	5110'	5500'



Gnd speed-Kts	70	90	100	120	140	160	8500'	 RT	 AG766
Descent Angle 3.40°	421	541	602	722	842	963			
MAP at RW34 or FAF to MAP	5.0	4:17	3:20	3:00	2:30	2:09			

STRAIGHT-IN LANDING RWY 34

MISSED APCH CLIMB GRADIENT MIM 4.5%

LNAV

MDA(H) 4430' (803')

CIRCLE-TO-LAND

MISSED APCH CLIMB GRADIENT MIM 4.5%

Max

Kts

MDA(H)

4500' (829') -2800m

NOT APPLICABLE


CHANGES: Airport name.

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

SLAL
Apt Elev 10184'
S19 14.3 W065 08.9

18 OCT 19 (20-9)

SUCRE, BOLIVIA
ALCANTARI



ADDITIONAL RUNWAY INFORMATION

RWY		USABLE LENGTHS		TAKE-OFF	WIDTH
		Threshold	Landing Beyond		
18	HIRL				148'
36	HIRL PAPI-L (3.3°)				45m
TAKE-OFF					
	All Rwys				
1 & 2 Eng	1600m				
3 & 4 Eng	800m				

CHANGES: Communications, location name, lighting.

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

SLAL
ALCANTARI

MISSED APCH CLIMB
GRADIENT MIM 4.0%

18 OCT 19

(21-1)

CAT A, B & C

SUCRE, BOLIVIA
ILS Z Rwy 36

*ALCANTARI Approach
119.1

*ALCANTARI Tower
118.4

*Ground
121.9


LOC
ILCA
109.9

Final
Apch Crs
359°

GS
D10.4 ILCA
13800' (3625')

ILS
DA(H)
10575' (400')


Apt Elev 10184'
Rwy 10175'




MISSED APCH: Intercept ALC VOR R-359 outbound climbing to 15000' direct to EGLAP/ D25.0 ALC VOR, enter hold and request instructions from ATC.

Alt Set: INCHES Rwy Elev: 321 hPa Trans level: By ATC Trans alt: 16000'

1. DME required. 2. MAX 160 KT.



ILCA DME	1.1	3.0	5.0	7.0	10.4
ALTITUDE	10575'	11230'	11930'	12630'	13800'



Gnd speed-Kts	70	90	100	120	140	160	PAPI-L	15000' on 113.4 R-359	D➔	EGLAP	
GS	3.30°	409	526	584	701	817					934
MAP at DA											

STRAIGHT-IN LANDING RWY 36
Missed Apch Climb Gradient Mim 4.0%

CIRCLE-TO-LAND
Missed Apch Climb Gradient Mim 4.0%

ILS
DA(H) 10575' (400')

Max Kts	MDA(H)
100	11680' (1496') -2400m
135	11780' (1596') -2800m
180	11880' (1696') -4400m

A	2000m
B	2400m
C	4000m
D	NOT APPLICABLE

NOT APPLICABLE

CHANGES: Communications, location name, PAPI-L added.

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE


SLAL
ALCANTARI

18 OCT 19 (22-1)


MISSED APCH CLIMB
GRADIENT MIM 5.0%

SUCRE, BOLIVIA
RNAV (GNSS) Z Rwy 36

*ALCANTARI Approach 119.1		*ALCANTARI Tower 118.4		*Ground 121.9	
RNAV	Final Apch Crs 358°	Minimum Alt AL424 11980' (1805')	LNAV MDA(H) 10920' (745')	Apt Elev 10184' Rwy 10175'	TAA 25 NM IAF
MISSED APCH: Climb to 15000' direct to EGLAP to join holding pattern and request instructions from ATC.					
Alt Set: INCHES Rwy Elev: 321 hPa Trans level: By ATC Trans alt: 16000'					
1. GNSS required. 2. MAX 185 KT.					



DIST to MAP	3.0	2.0	1.0
ALTITUDE	11980'	11630'	11270'






Gnd speed-Kts	70	90	100	120	140	160	PAPI-L	15000'	D	EGLAP
Descent Angle 3.30°	409	526	584	701	817	934				
MAP at AL423 or FAF to MAP	5.0	4:17	3:20	3:00	2:30	2:09				

STRAIGHT-IN LANDING RWY 36 MISSED APCH CLIMB GRADIENT MIM 5.0%						CIRCLE-TO-LAND			
LNAV MDA(H) 10920' (745')									
A	2000m					Max Kts	MDA(H)		
B	2400m					100	11680' (1496') -2400m		
C	4000m					135	11680' (1496') -2800m		
D	4400m					180	11780' (1596') -4400m		
						205	11880' (1696') -4800m		

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

SUCRE, BOLIVIA
VOR Z Rwy 36

*ALCANTARI Approach 119.1		*ALCANTARI Tower 118.4		*Ground 121.9	
VOR ALC 113.4	Final Apch Crs 358°	Minimum Alt D5.0 12270' (2095')	MDA(H) 10960' (785')	Apt Elev 10184' Rwy 10175'	 MSA ALC VOR
MISSED APCH: Maintain course 358° climbing to 15000' direct to EGLAP/D25.0/R-358 ALC, enter holding and request instructions from ATC.					
Alt Set: INCHES Rwy Elev: 321 hPa 1. DME required. 2. MAX 185 KT.		Trans level: By ATC Trans alt: 16000'			



Gnd speed-Kts	70	90	100	120	140	160	15000' ↑ PAPI-L on ALC 113.4 R-358 → EGLAP
Descent Angle 3.33°	412	530	589	707	825	943	
MAP at D1.3 or							
FAF to MAP 3.7	3:10	2:28	2:13	1:51	1:35	1:23	

STRAIGHT-IN LANDING RWY 36 MISSED APCH CLIMB GRADIENT MIN 4.5% MDA(H) 10960' (785')		Max Kts	CIRCLE-TO-LAND MDA(H) _____
A	2000m	100	11680' (1496') - 2400m
B	2400m	135	11680' (1496') - 2800m
C	4000m	180	11780' (1596') - 4400m
D	4400m	205	11880' (1696') - 4800m

CHANGES: Communications, location name, PAPI-L added.


PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

SLAL ALCANTARI

18 OCT 19 **(23-2)**

MISSED APCH CLIMB
GRADIENT MIM 4.5%


SUCRE, BOLIVIA
VOR Y Rwy 36



PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

Ap1 Elev
8360'


Alt1 Set: hPa Trans level: By ATC Trans alt: 18000'




PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

Apt Elev
8360'

Trans level: By ATC Trans alt: 18000'
1. CBA DME required. 2. ADF required.



MOSGO 2 [MOSGO2], PUNAV 2 [PUNAV2],
TEDOK 2 [TEDOK2], TEREK 2 [TEREK2]
DEPARTURES
(RWY 14)



These SIDs require minimum climb gradients:
4.1% to 9800', 5.8% to VUKRI, then 4.1% to BITEV.

Gnd speed-KT	75	100	150	200	250	300
4.1% V/V (fpm)	311	415	623	830	1038	1246
5.8% V/V (fpm)	441	587	881	1175	1468	1762


INITIAL CLIMB

After take-off, MAINTAIN runway heading to D7.0 CBA, climbing to at or above 9800'. Turn RIGHT to 166° course to VUKRI. Turn RIGHT on D15.0 Arc CBA to BITEV.

SID	ROUTING
MOSGO 2	After BITEV, turn RIGHT to 022° course to CBB NDB. Intercept 356° course direct to MOSGO.
PUNAV 2 (W-12, UW-12)	After BITEV, turn RIGHT to 022° course to CBB NDB. Intercept 045° course direct to PUNAV.
TEDOK 2 (UM-793, UW-677)	After BITEV, 325° course to TEDOK.
TEREP 2 (W-11)	After BITEV, 315° course to TEREP.

CHANGES: Airway W-2 removed.

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE




CHANGES: Airway W-2 removed.

Apt Elev
8360'

Trans level: By ATC
GNSS required.



Trans alt: 18000'



MUNET 2 RNAV (GNSS) DEPARTURE

[MUNET2]

(RWYS 14, 32)



This SID requires minimum climb gradients:

Rwy 14: 4.1% to CB367, then 5.8% to PORKI.

Rwy 32: 4.6% to CB363.

Gnd speed-KT	75	100	150	200	250	300
4.1% V/V (fpm)	311	415	623	830	1038	1246
4.6% V/V (fpm)	349	466	699	932	1165	1398
5.8% V/V (fpm)	441	587	881	1175	1468	1762

INITIAL CLIMB


RWY	INITIAL CLIMB
14	After take-off, MAINTAIN runway heading to CB367. MAINTAIN 141° course to PORKI.
32	After take-off, MAINTAIN runway heading to CB363. Turn LEFT 135° course to PORKI.
ROUTING	
At PORKI, turn LEFT on 098° course to MUNET.	

At PORKI, turn LEFT on 098° course to MUNET.

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE


Apt Elev
8360'

Trans level: By ATC Trans alt: 18000'
1. CBA DME required. 2. ADF required.



MSA CBB NDB

**TEDOK 3 [TEDOK3], TERE3 [TEREP3]
DEPARTURES
(RWY 32)**



Gnd speed-KT	75	100	150	200	250	300
4.2% V/V (fpm)	319	425	638	851	1063	1276
4.6% V/V (fpm)	349	466	699	932	1165	1398

These SIDs require minimum climb gradients: 4.6% to 8950', then 4.2% to PALOT.

INITIAL CLIMB

After take-off, MAINTAIN runway heading to D3 CBA, climbing to 8950'. Turn LEFT to R NDB, intercept R 231° bearing to PALOT.

ROUTING

TEDOK 3 (UM-793, UW-677)	After PALOT, turn RIGHT on 338° course to TEDOK.
TEREP 3 (W-11)	After PALOT, turn RIGHT on 326° course to TEREP.

NOT TO SCALE

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

LOCAL FLIGHT RESTRICTIONS

GENERAL

Overflight of the city is strictly prohibited by the applicable Air Regulations without the express authorization of the Direccion Regional de Aeronautica Civil (ref. Reglamento Del Aire, Reglas Generales de Vuelo, Chapter IV, par 15, 1st insert).

RUNWAY 04

- a. Night operations are not authorized.
- b. During daylight operations, aircraft should always make a left turn on departure.
- c. Piston powered aircraft are not authorized for takeoff operations

RUNWAY 22

- a. Night takeoffs are not authorized except for flight schools conducting instructional flights, in which case the aircraft should always make a right turn on departure.
- b. After takeoff, a right turn on departure should always be made during daylight operations except for single-engine aircraft with a MTOW of less than 12,566 lbs (5700kg).
- c. After takeoff, a left turn or runway heading departure is not authorized, except for single engine aircraft with a MTOW of less than 12,566 lbs (5700kg).

RUNWAY	TAKEOFF		LANDING	
	DAY	NIGHT	DAY	NIGHT
04	Authorized (1)	Not Authorized	Authorized	Not Authorized
22	Authorized (2)	Not authorized except single engine aircraft.	Authorized	Authorized

NOTES:


- 1. Turns to the right and piston aircraft are Not Authorized.
- 2. Turns to the left are Not Authorized, except for single-engine aircraft.

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

Apt Elev **8360'**
S17 25.1 W066 10.6

10-9

COCHABAMBA, BOLIVIA
JORGE WILSTERMANN INTL




ADDITIONAL RUNWAY INFORMATION					USABLE LENGTHS		TAKE-OFF	WIDTH
RWY				LANDING BEYOND				
				Threshold	Glide Slope			
05	HIRL (60m)	PAPI-L (angle 3.3°)				4869' 1484m	148'	
	23	HIRL (60m)	PAPI-L (angle 3.10°)	7962'	2427m	8497' 2590m	45m	
14	HIRL (60m)	PAPI (angle 2.57°)		12139'	3700m	12139' 3700m	148'	
	32	HIRL (60m)	ALS PAPI-L (angle 3.3°)	11483'	3500m	10400' 3170m	11680' 3560m	45m
TAKE-OFF								
	All Rwys							
1 & 2 Eng	1600m							
3 & 4 Eng	800m							


CHANGES: Runway Idents, bearings, aprons, parking stands, taxiways.

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

COCHABAMBA Approach 119.3		COCHABAMBA Tower 118.1		Ground 121.9		*COCHABAMBA Radio 127.1	
LOC ILCO 110.5	Final Aptch Crs 321°	GS D8.6 ILCO (3048')	ILS DA(H) 8690' (338')	Apt Elev 8360' Rwy 8352'			
MISSED APCH: Maintain runway heading until D3.7 CBA climbing to 9600', turn LEFT heading 253° to R NDB, turn LEFT heading 157° continue climb to 16000' at 4.5% climb gradient, intercept CBA VOR R-202 direct to MOXIL and hold. Request instructions from ATC.							
Alt Set: hPa 1. DME required.		Rwy Elev: 271 hPa		Trans level: By ATC		Trans alt: 18000'	



LOC (GS out)	ILCO DME	1.0	2.0	3.0	4.0	5.0	6.0	7.0
	ALTITUDE	9040'	9390'	9750'	10100'	10450'	10800'	11150'



Gnd speed-Kts	70	90	100	120	140	160	ALS PAPI-L	9600' ↑ on	RWY hdg	D3.7 CBA 112.1	
GS	3.30°	409	526	584	701	817					934
MAP at D0.8 ILCO or FAF to MAP	7.8	6:41	5:12	4:41	3:54	3:21					2:56

STRAIGHT-IN LANDING RWY 32 Missed apch climb gradient mim 4.0% ILS LOC (GS out)				CIRCLE-TO-LAND Missed apch climb gradient mim 4.0%			
DA(H)	8690' (338')	MDA(H) 9560' (1208')		Max Kts	MDA(H)	VIS	
	FULL	ALS out	ALS out				
A	1600m	2400m	1600m	2400m	100	10600' (2240')	2600m
B		2800m	2000m	2800m	135	10600' (2240')	2800m
C	2400m	4800m	4000m	4800m	180	11200' (2840')	4800m
D			4400m		205		

CHANGES: Bearings, database waypoints, GS angle.


PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE



SLCB/CBB
JORGE WILSTERMANN
INTL

31 MAY 19

(11-2)

COCHABAMBA, BOLIVIA
MISSED APCH CLIMB
GRADIENT MIM 4.0% ILS Y RWY 32

BRIEFING STRIP™	COCHABAMBA Approach 119.3		COCHABAMBA Tower 118.1		Ground 121.9	*COCHABAMBA Radio 127.1
	LOC ILCO 110.5	Final Apch Crs 321°	GS D8.6 ILCO 11400' (3048')	ILS DA(H) 8690' (338')	Apt Elev 8360' Rwy 8352'	
	MISSED APCH: Maintain runway heading until D3.7 CBA climbing to 9600', turn LEFT heading 253° to R NDB, turn LEFT heading 157° continue climb to 16000' at 4.5% climb gradient, intercept CBA VOR R-202 direct to MOXIL and hold. Request instructions from ATC.					
	Alt Set: hPa		Rwy Elev: 271 hPa		Trans level: By ATC	
	1. DME required.				Trans alt: 18000'	
						MSA CBA VOR



LOC (GS out)	ILCO DME ALTITUDE	1.0	2.0	3.0	4.0	5.0	6.0	7.0
		9040'	9390'	9750'	10100'	10450'	10800'	11150'
D8.6 ILCO GS 11400'								
ESNAZ 141° → ← 321° D21.0/CBA D16.0 CBA 17000' → ← 321° 14000' 141° → ← 321° 12800' → ← 321°								
TCH 50' → ← 321° 11400' → ← 321°								
Rwy 8352' → ← 0.6 7.8 6.7								

Gnd speed-Kts	70	90	100	120	140	160	ALS PAPI-L		9600' on	RWY	D3.7 CBA
GS	3.30°	409	526	584	701	817				Hdg	112.1
MAP at D0.8 ILCO or FAF to MAP	7.8	6:41	5:12	4:41	3:54	3:21					

STRAIGHT-IN LANDING RWY 32 Missed Apch Climb Gradient Mim 4.0% ILS						CIRCLE-TO-LAND Missed Apch Climb Gradient Mim 4.0%		No Circling
DA(H) 8690' (338')		LOC (GS out)		MDA(H) 9560' (1208')				
FULL	ALS out	FULL	ALS out	FULL	ALS out	Max Kts	VIS	
A	1600m	2400m	1600m	2400m	2400m	100	10600' (2240')	2600m
B		2800m	2000m	2800m	2800m	135	10600' (2240')	2800m
C			4000m		4800m	180		
D	2400m	4800m	4400m	4800m	4800m	205	11200' (2840')	4800m

CHANGES: Bearings, GS angle, profile.


PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

SLCB/CBB MISSED APCH CLIMB
GRADIENT MIM 5.0%
JORGE WILSTERMANN INTL 3 MAY 19 (12-1)


COCHABAMBA, BOLIVIA
RNAV (GNSS) Z Rwy 32

UNCLAS E F O U N D

COCHABAMBA Approach 119.3		COCHABAMBA Tower 118.1		Ground 121.9		*COCHABAMBA Radio 127.1	
RNAV	Final Apch Crs 321°	Minimum Alt CB745 9700' (1348')	LNAV MDA(H) 8800' (448')	Apt Elev 8360' Rwy 8352'		TAA 25 NM IAF	
MISSED APCH: Climb to 10300' direct to CB747, turn LEFT to CB748 and climb to 16000'. Enter hold, 021° inbound, LEFT turns, and request instructions from ATC.							
Alt Set: hPa		Rwy Elev: 271 hPa		Trans level: By ATC			
1. GNSS required. 2. PAPI and descent angle not coincident.							



DIST to THR	1.0	2.0	3.0	4.0
ALTITUDE	8720'	9040'	9360'	9700'



Gnd speed-Kts	70	90	100	120	140	160	ALS PAPI-L		10300'	→ CB747
Descent Angle 3.10°	384	494	548	658	768	878			↑	
MAP at RW32										
FAF to MAP	4.0	3:26	2:40	2:24	2:00	1:43				

STRAIGHT-IN LANDING RWY 32 Missed apch climb gradient mim 5.0% LNAV MDA(H) 8800' (448')			CIRCLE-TO-LAND Missed apch climb gradient mim 5.0%		
		ALS out	Max Kts	MDA(H)	
A	1600m	2000m	100	9900' (1541') - 2400m	
B			135		
C	2000m	2400m	180	10700' (2341') - 3200m	
D	2800m	3200m	205	12100' (3741') - 4400m	

CHANGES: New procedure.

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

SLCB/CBB

JORGE WILSTERMANN INTL 31 MAY 19

(13-1)

MISSED APCH CLIMB
GRADIENT MIM 3.0%

COCHABAMBA, BOLIVIA

VOR Z Rwy 14

COCHABAMBA Approach

COCHABAMBA Tower

Ground

*COCHABAMBA Radio

119.3

118.1

121.9

127.1

VOR

Final

Minimum Alt

MDA(H)

Apt Elev 8360'


CBA
112.1Apch Crs
144°D7.0
10590' (2236')

8950' (596')


Rwy 8354'

MISSED APCH: Climb on heading 144° to CBA VOR, ascend to 9200' with minimum 3.0% climb gradient, intercept outbound CBA VOR R-142 and climb to 16000' at 4.9% climb gradient direct to PORKI. Contact ATC for instructions.

Alt Set: hPa Rwy Elev: 271 hPa Trans level: By ATC Trans alt: 18000'
1. DME required. 2. CAUTION: High obstacles beyond 10 DME arc, sector W-NW-N from airport. Remain within 7 DME ARC.



MSA CBA VOR



CBA DME

5.5

4.5

3.5

ALTITUDE

10050'

9680'

9315'

PALOT

D20.0

D9.0

[D2451]

D5.5

[FD14]

VOR

1.5 065° ← 245°
Min MANDATORY
17000'

065°

13700'

10050'

7 DME Arc

11.0

144°

3.43%

3.0

1.5'

Rwy 8354'

TCH 50'

CBA

on 112.1

R-142

Gnd speed-Kts

70

90

100

120

140

160

Descent Angle

3.43°

425

546

607

728

850

971

MAP at D2.5 or

FAF to MAP

3.0

2:34

2:00

1:48

1:30

1:17

1:08

PAPI

9200'

on 112.1

R-142

STRAIGHT-IN LANDING RWY 14

Missed apch climb gradient mim 3.0%

MDA(H) 8950' (596')

CIRCLE-TO-LAND

Missed apch climb gradient mim 3.0%

No Circling

A

B

C

D

1600m

2800m

3200m

Max

Kts

100

135

180

205

MDA(H)

11400' (3040')

11400' (3040')

12000' (3640')

12000' (3640')

vis.

2000m

3200m

3600m

4400m

4800m

2400m

2800m


3200m

3600m

4000m

4400m

4800m



PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

CHANGES: Bearings, descent angle.

SLCB/CBB

JORGE WILSTERMANN INTL

4 OCT 19

(13-3)

MISSED APCH CLIMB
GRADIENT MIM 4.0%

COCHABAMBA, BOLIVIA

VOR A Rwy 14

COCHABAMBA Approach

119.3

COCHABAMBA Tower

118.1

Ground

121.9

*COCHABAMBA Radio

127.1

VOR

CBA

112.1

Final

Apch Crs

064°

No FAF

Refer to

Minimums

Apt Elev 8360'

Rwy 8354'

MISSED APCH: Climbing LEFT turn to intercept CBA VOR R-140 outbound within 3 DME, ascend to 16000' direct to PORKI and enter hold.
Contact ATC for instructions.

Alt Set: hPa




Rwy Elev: 271 hPa

Trans level: By ATC

Trans alt: 18000'

1. DME required. 2. CAUTION: High obstacles beyond 10 DME arc, sector W-NW-N from airport.

MSA CBA VOR




					PAPI	140° LT	CBA within 112.1 3.0 DME	16000'
MAP at VOR								

CIRCLE-TO-LAND

Missed Apch Climb Gradient Mim 4.0%

No Circling

	Max Kts	MDA(H)	VIS
A	100	11000' (2640')	2400m
B	135	11000' (2640')	2800m
C	180	11000' (2640')	4400m
D	205	11000' (2640')	4800m



PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

CHANGES: None

4 OCT 19

13-4

COCHABAMBA, BOLIVIA
MISSED APCH CLIMB
GRADIENT MIM 4.0% VOR V Rwy 32

VOR V Rwy 32

COCHABAMBA Approach	COCHABAMBA Tower	Ground	*COCHABAMBA Radio
119.3	118.1	121.9	127.1



VOR CBA 112.1	Final ApcH Crs 321°	Minimum Alt D10.0 11800' (3448')	MDA(H) 9560' (1208')	Apt Elev 8360' Rwy 8352'	
----------------------------	----------------------------------	---	--------------------------------	-----------------------------	---

MISSED APCH: Maintain heading 321° and climb to 11000' direct to D4.0 CBA. Then turn LEFT to R NDB, turn LEFT heading 157° and climb to 16000' to intercept CBA VOR R-202 outbound direct to MOXIL and hold. Request instructions from ATC.


Alt Set: hPa	Rwy Elev: 271 hPa	Trans level: By ATC	Trans alt: 18000'
--------------	-------------------	---------------------	-------------------

DME required.

MSA CBA VOR



CBA DME	5.0	6.0	7.0	8.0	9.0
ALTITUDE	9930'	10300'	10680'	11050'	11420'



Gnd speed-Kts	70	90	100	120	140	160	HIALS PAPI-L 
Descent Angle	3.49°	432	556	618	741	865	
MAP at D4.0							

STRAIGHT-IN LANDING RWY 32

Missed Apch Climb Gradient Mim 4.0%

MDA(H) **9560'** (1208')

CIRCLE-TO-LAND

Missed Apch Climb Gradient Mim 4.0%

MDA(H) 9560' (1208')			Max Kts	MDA(H)
		ALS out		
A	1600m	2400m	100	10600' (2240') -2600m
B	2000m	2800m	135	10600' (2240') -2800m
C	4000m	4800m	180	11200' (2840') -4800m
D	4400m		205	

CHANGES: Re-indexed.

PARA USO EN AVIACION VIRTUAL ÚNICAMENTE

SLCO/CIJ
CAP AV CIV ANIBAL
ARAB FADUL

27 JAN 17

10-3

Eff 2 Feb

COBIJA, BOLIVIA

RNAV SID

Apt Elev
804'

Trans level: By ATC
GNSS required. Trans alt: 5000'


3000'

MSA ARP

AKRUD 1 (RNAV GNSS) DEPARTURE

[AKRUD1]
(RWY 20)

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE



INITIAL CLIMB

After take-off MAINTAIN runway heading to cross CO612 at or above 2450'. Continue climb on course 199° to AKRUD, cross AKRUD at or above FL050.

CHANGES: New procedure at this airport.

SLCO/CIJ
CAP AV CIV ANIBAL
ARAB FADUL

27 JAN 17

10-3A


Eff 2 Feb

COBIJA, BOLIVIA

SID


Apt Elev
804'

Trans level: By ATC Trans alt: 5000'
ADF required.



GAXAN 1 DEPARTURE

[GAXAN1]
(RWY 20)



This SID requires a climb gradient of 3.5% to GAXAN.

Gnd speed-KT	75	100	150	200	250	300
3.5% V/V (fpm)	266	354	532	709	886	1063

INITIAL CLIMB

After take-off MAINTAIN runway heading to 1200' or above, turn LEFT heading 138° and intercept CIJ 168° bearing to GAXAN. Cross GAXAN at or above FL050.

CHANGES: New procedure at this airport.

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

SLCO/CIJ
CAP AV CIV ANIBAL
ARAB FADUL

27 JAN 17

10-3B

Eff 2 Feb

COBIJA, BOLIVIA

RNAV SID

Apt Elev
804'


Trans level: By ATC
GNSS required. Trans alt: 5000'

GAXAN 2 (RNAV GNSS) DEPARTURE
[GAXAN2]
(RWY 20)

3000'

MSA ARP

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE



INITIAL CLIMB


After take-off MAINTAIN runway heading to cross CO612 at or above 2450'. After CO612 turn LEFT course 150° to GAXAN, cross GAXAN at or above FL050.

CHANGES: New procedure at this airport.

Apt Elev **804'**
S11 02.4 W068 47.0

14 JUL 17 (10-9)

COBIJA, BOLIVIA
CAP AV CIV ANIBAL ARAB FADUL

[illegible]

CHANGES: Take-off minimums.

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

23 NOV 12


SLCO/CIJ

CAT A, B & C

COBIJA, BOLIVIA

CAP AV CIV ANIBAL ARAB FADUL INTL (12-1)

RNAV (GNSS) Z Rwy 02



PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

SLCO/CIJ

23 NOV 12

COBIJA, BOLIVIA

CAP AV CIV ANIBAL ARAB FADUL INTL (16-1)

CAT B & C

NDB-2 Rwy 02

BRIEFING STRIP™

LA PAZ Control

128.2

*COBIJA Approach

118.3

*COBIJA Tower

118.3

NDB

CIJ

*230

Final

Apch Crs

022°

No FAF

MDA(H)

(CONDITIONAL)

1200' (396')

Apt Elev 804'

Rwy 02 804'

MISSED APCH: Maintain bearing 022° to CIJ NDB, then turn LEFT to 245° heading climbing to 2000'. Request instructions from CONTROL.

Alt Set: hPa

Rwy Elev: 29 hPa

Trans level: By ATC

Trans alt: 5000'

1. Procedure not authorized at night.

MSA CIJ NDB

2000'

LA PAZ Control

128.2

*COBIJA Approach

118.3

*COBIJA Tower

118.3

NDB

CIJ

*230

Final

Apch Crs

022°

No FAF

MDA(H)

(CONDITIONAL)

1200' (396')

Apt Elev 804'

Rwy 02 804'

MISSED APCH: Maintain bearing 022° to CIJ NDB, then turn LEFT to 245° heading climbing to 2000'. Request instructions from CONTROL.

Alt Set: hPa

Rwy Elev: 29 hPa



Trans level: By ATC

Trans alt: 5000'

1. Procedure not authorized at night.

MSA CIJ NDB

2000'



Gnd speed-Kts	70	90	100	120	140	160		CIJ *230 022°	CIJ *230	LT	245° hdg	2000'
Descent Gradient 4.2%	298	383	425	510	595	681						
MAP at MDA												

STRAIGHT-IN LANDING RWY 02

MDA(H) 1200' (396')

CIRCLE-TO-LAND 20

Not Authorized West of Airport

PANS OPS	A	NOT APPLICABLE	Max Kts.	A	NOT APPLICABLE
	B	1600m	135		1300' (496') - 1600m
	C		180		1400' (596') - 2400m
	D	NOT APPLICABLE	D		NOT APPLICABLE


CHANGES: Approach freq added.

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

Apt Elev
1371'

Trans level: By ATC Trans alt: 5000'

ANBUN 1 [ANBUN1], LIVON 1 [LIVON1]
LODAK 1 [LODAK1] DEPARTURES
(RWY 15)



VIRU VIRU
 D 113.8 VIR


 \$17 37.6 W063 08.9

TROMPILLO
265 TCZ

S17 48.2 W063 10.4



NOT TO SCALE



INITIAL CLIMB

After take-off intercept TCZ 149° bearing to PULKO.


SID	ROUTING
ANBUN 1	From PULKO, 221° course to ANBUN.
LIVON 1 (T-554)	From PULKO, 218° course to LIVON.
LODAK 1 (W-8, UW-316)	From PULKO, 236° course to LODAK.

CHANGES: None.


PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

Apt Elev
1371'

Trans level: By ATC Trans alt: 5000'



GAVOS 1 [GAVOS1], SIKIN 1 [SIKIN1] DEPARTURES
(RWY 15)




VIRU VIRU
D 113.8 VIR
S17 37.6 W063 08.9



TROMPILLO
265 TCZ
S17 48.2 W063 10.4

6 NM from TCZ
At or above
1800'



27

134° D35.0

099°

103°

PALAG

49 SIKIN 1

116°

114°

D80.0

D80.0

At or above
FL070

SIKIN

A304

T543

At or above
FL070

GAVOS

At or above
FL070

GAVOS 1

48

INITIAL CLIMB

After take-off, turn LEFT, intercept TCZ 148° bearing to 6 NM from TCZ NDB. Then, 109° course to PALAG.

ROUTING

GAVOS 1 (T-543) From PALAG, 103° course to GAVOS. Cross GAVOS at or above FL070.


SIKIN 1 (A-304) From PALAG, 099° course to SIKIN. Cross SIKIN at or above FL070.

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

SLET/SRZ
Apt Elev 1371'
S17 48.7 W063 10.3

28 JUL 17 (10-9)

SANTA CRUZ, BOLIVIA
EL TROMPILLO



PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

ADDITIONAL RUNWAY INFORMATION					
RWY		USABLE LENGTHS		TAKE-OFF	WIDTH
		Threshold	Glide Slope		
15	33	RL	8159' 2487m		98'
			8199' 2499m		30m
TAKE-OFF					
	All Rwys				
1 & 2 Eng	1600m				
3 & 4 Eng	800m				

CHANGES: Take-off minimums, magnetic variation, airport elevation.


SLET/SRZ
EL TROMPILLO

2 JUN 17

12-1

CAT A, B & C

SANTA CRUZ, BOLIVIA
RNAV (GNSS) Z Rwy 33




PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

SLGM
Apt Elev **460'**
S10 53.3 W065 22.9

28 JUL 17 **(12-1)**

GUAYARAMERIN, BOLIVIA
GUAYARAMERIN INTL



ADDITIONAL RUNWAY INFORMATION					
RWY		USABLE LENGTHS		TAKE-OFF	WIDTH
		Threshold	Glide Slope		
16	34				69' 21m
TAKE-OFF					
	All Rwy's				
1 & 2 Eng	1600m				
3 & 4 Eng	800m				

CHANGES: Take-off minimums.

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE


SLGM
GUAYARAMERIN INTL

28 JUL 17

(12-1)

CAT A & B

GUAYARAMERIN, BOLIVIA
RNAV (GNSS) Z Rwy 34




PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

SLHI/CCA
Apt Elev 752'
S16 58.7 W065 08.7

4 OCT 19 (20-9)

COCHABAMBA, BOLIVIA
CHIMORE



ADDITIONAL RUNWAY INFORMATION					
RWY		LANDING BEYOND		TAKE-OFF	WIDTH
		Threshold	Glide Slope		
17	35	11,988' 3654m			148' 45m


TAKE-OFF	
All Rwys	
1 & 2 Eng	1600m
3 & 4 Eng	800m


PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

SLHI/CCA
CHIMORE


2 DEC 16
Eff 8 Dec 22-1

MISSED APCH CLIMB GRADIENT MIM 3.0% COCHABAMBA, BOLIVIA
CAT A, B & C RNAV (GNSS) Y Rwy 17

BRIEFING STRIP ™	LA PAZ Control 128.2			CHIMORE Tower 118.4		
	RNAV	Final Apch Crs 173°	Minimum Alt HI875 2700' (1974')	LNAV MDA(H) 1200' (474')	Apt Elev 752' Rwy 726'	
	MISSED APCH: Turn LEFT direct to HI874, climb to 4000' to hold, and request ATC instructions.					
	Alt Set: hPa Rwy Elev: 26 hPa Trans level: By ATC Trans alt: 5000'					
	1. GNSS required. 2. CAUTION: Hills and trees in the missed approach path at 2.6 NM from threshold 17 at 647'. 3. PAPI and RNAV glide path not coincidental.					
MSA ARP						



DIST to THR	4.4	4.0	3.0	2.0	1.0
ALTITUDE	2700'	2500'	2160'	1820'	1480'




Gnd speed-Kts	70	90	100	120	140	160	4000' LT D→ HI874	
Descent angle	3.20°	396	510	566	679	793		906
MAP at HI873								
FAF to MAP	4.4	3:46	2:56	2:38	2:12	1:53		1:39

STRAIGHT-IN LANDING RWY 17 MISSED APCH CLIMB GRADIENT MIM 3.0% LNAV MDA(H) 1200' (474')					CIRCLE-TO-LAND				
A	2400m				Max Kts	A	NOT APPLICABLE		
B						B			
C	2800m					C			
D	NOT APPLICABLE					D			

CHANGES: New procedure.

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

Alt Elev 13314	All Set HPa Trans level: By ATC
ARRIVALS	



PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

Trans alt: 18000

19000
17000
15000

CONTOUR INTERVALS

23 1

224

18,000

NOT TO SCALE

ARPIS
FL190

LONAB
FL050




PAZ VOR

RWY	INITIAL CLIMB
10	After take-off, MAINTAIN runway heading to D5.5 PAZ, turn RIGHT heading 220°.
28	After take-off, MAINTAIN runway heading to 13500, turn LEFT heading 140°.
SID	ROUTING
ARPIS 7 (W-6, UW-6)	Intercept PAZ R153 direct to ARPIS.
LONAB 1	Intercept PAZ R166 direct to LONAB.

Apt Elev 13314
Trans alt: 18000
ADF-DME required.


ARPIS 8 [ARPIS8], LONAB 2 [LONAB2]
DEPARTURES




RWY		INITIAL CLIMB
10		After take-off continue on 106° course to D1.8 LPZ, turn RIGHT.
28		After take-off MAINTAIN runway heading to D4.4 LPZ, turn LEFT on D7.0 Arc LPZ.
SID	RWY	ROUTING
ARPIS 8 (UW-6, W-6)	10	Intercept LPZ 157° bearing direct to ARPIS.
	28	MAINTAIN D7.0 Arc LPZ to intercept LPZ 157° bearing direct to ARPIS.
LONAB 2	10	Intercept LPZ 170° bearing direct to LONAB.
	28	MAINTAIN D7.0 Arc LPZ to intercept LPZ 170° bearing direct to LONAB.

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE




CHANGES: Airway UA 304 removed.



CHANGES: Airway UA 304 removed.

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE



PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE


SLLP/LPB
EL ALTO INTL

17 MAY 19


10-3E

LA PAZ, BOLIVIA

SID



CHANGES: Airway UA 304 removed.




PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

Apt Elev
13314

Trans alt: 18000

ELAMU 1 [ELAMU1], KIBUX 1 [KIBUX1]
DEPARTURES




PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

RWY	INITIAL CLIMB
10	After take-off, MAINTAIN runway heading to D5.5 PAZ, turn RIGHT to PAZ VOR and intercept PAZ R334 to IRIBI.
28	After take-off, MAINTAIN runway heading to 13500, turn RIGHT to intercept PAZ R334 to IRIBI.
SID	ROUTING
ELAMU 1 (T-711, UL-309, UT-711)	After IRIBI, 033° course to ELAMU.
KIBUX 1	After IRIBI, 355° course to KIBUX.

Apt Elev 13314	Trans alt: 18000
-------------------	------------------


ELAMU 2 [ELAMU2] DEPARTURE



RWY	INITIAL CLIMB
10	After take-off, MAINTAIN runway heading to D5.5 PAZ. Turn RIGHT heading 180° to 16200. Turn RIGHT to intercept PAZ R164 to PAZ VOR.
28	After take-off, MAINTAIN runway heading to 13500. Turn LEFT to intercept PAZ R212 to 16200. Turn LEFT to intercept PAZ R192 to return to PAZ VOR.
ROUTING	
At PAZ VOR, intercept PAZ R010 direct to ELAMU.	

Trans alt: 18000
ADF-DME required.

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE




RWY	INITIAL CLIMB
10	After take-off continue on 106° course to D1.8 LPZ, turn RIGHT to intercept LPZ 151° bearing to at or above 16200, turn RIGHT track 006° to return to LPZ NDB.
28	After take-off MAINTAIN runway heading to D4.4 LPZ, turn LEFT to intercept LPZ 225° bearing to at or above 16200, turn LEFT track 006° to return to LPZ NDB.
SID	ROUTING
ELAMU 3 (T-711, UL-309, UT-711)	At LPZ NDB, MAINTAIN LPZ 006° bearing direct to ELAMU.
KIBUX 2	At LPZ NDB, MAINTAIN LPZ 342° bearing direct to KIBUX.

Apt Elev
13314


Trans alt: 18000

IROBO 1 [IROBO1], KOVIS 1 [KOVIS1]
TEGUM 1 [TEGUM1] DEPARTURES



RWY	INITIAL CLIMB
10	MAINTAIN runway heading to D5.5 PAZ, turn RIGHT to PAZ VOR.
28	MAINTAIN runway heading to 13500. Turn LEFT.
SID	ROUTING
IROBO 1 (UL-309)	Intercept PAZ R193 direct to IROBO.
KOVIS 1 (A-573, UA-573)	Intercept PAZ R247 direct to KOVIS.
TEGUM 1 (A-568, UM-664)	Intercept PAZ R234 direct to TEGUM.

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE



PARA USO EN AVIACIÓN VIRTUAL UNICAMENTE




PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

Apt Elev
13314

INITIAL CLIMB		ROUTING	
After take-off, MAINTAIN runway heading to 15000. Turn left to intercept PAZ R250 to D11.0 PAZ. Turn left to intercept PAZ R225 to PAZ VOR. Intercept PAZ R064 and MAINTAIN 7000 to D5.0 PAZ. Continue climbing to D15.0 PAZ. to CRC NDB.			
SID		ROUTING	
REDIR 1		From CRC NDB, continue on 043° course direct to REDIR.	
RENOP 1 (W-10)		From CRC NDB, continue on 014° course direct to RENOP.	
SALVO 1 (W-9)		From CRC NDB, continue on 071° course direct to SALVO.	

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE




PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

SLLP/LPB
Apt Elev **13314'**
S16 30.8 W068 11.0

4 OCT 19 **(10-9)**

LA PAZ, BOLIVIA
EL ALTO INTL



ADDITIONAL RUNWAY INFORMATION

		USABLE LENGTHS			
RWY		LANDING BEYOND		TAKE-OFF	WIDTH
		Threshold	Glide Slope		
10	HIRL ALS REIL PAPI-L (angle 2.4°)		12,056' 3675m		151' 46m
28	HIRL REIL PAPI-L (angle 3.2°)				

TAKE-OFF

All Rwys

1 & 2 Eng	1600m
3 & 4 Eng	800m

CHANGES: Ramp, buildings, airport beacon moved, parking spots.

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

SLLP/LPB EL ALTO INTL

31 MAY 19 **(11-1)**

LA PAZ, BOLIVIA
ILS Z Rwy 10

BRIEFING STRIP™


10

5


0

5

LA PAZ Approach		LA PAZ Tower		Ground	
119.5		118.3		121.9	
LOC ILPA 110.3	Final Apch Crs 100°	Minimum Alt D7.2 ILPA 15000' (1889')	ILS DA(H) 13331' (220')	Apt Elev 13314' Rwy 13111'	
MISSED APCH: Turn RIGHT and intercept PAZ VOR R-181 outbound to D20.0 PAZ climbing to 17000' and hold. Request instruction from ATC.					
Alt Set: hPa		Rwy Elev: 397 hPa		Trans level: By ATC	
1. DME required. 2. MAX 160 KT.				Trans alt: 18000'	



RECOMMENDED ALTITUDES	
LOC (GS out)	
DIST to THR	ALTITUDE
7.0	14950'
6.0	14700'
5.0	14440'
4.0	14190'
3.0	13930'
2.0	13680'



Gnd speed-Kts	70	90	100	120	140	160	ALS	PAZ	17000'
GS	2.40°	297	382	424	509	594	679	115.7	R-181
MAP at VOR									

STRAIGHT-IN LANDING RWY 10				CIRCLE-TO-LAND	
ILS		LOC (GS out)			
DA(H) 13331' (220')		MDA(H) 13550' (439')			
FULL		ALS out			
A				Max Kts	MDA(H)
B				100	14050' (736') -2000m
C	1200m	1600m	1600m	135	14050' (736') -2400m
D		2000m	2000m	180	14660' (1346') -4000m
				205	15130' (1816') -4400m

PANS OPS

CHANGES: Procedure.

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE



SLLP/LPB EL ALTO INTL

31 MAY 19 **(11-2)**



LA PAZ, BOLIVIA
ILS Y Rwy 10

BRIEFING STRIP™

LA PAZ Approach 119.5		LA PAZ Tower 118.3		Ground 121.9
LOC ILPA 110.3	Final Apch Crs 100°	Minimum Alt D7.2 ILPA 15000' (1889')	ILS DA(H) 13331' (220')	Apt Elev 13314' Rwy 13111'
MISSED APCH: Turn RIGHT and intercept PAZ VOR R-181 outbound to D20.0 PAZ climbing to 17000' and hold. Request instruction from ATC.				
Alt Set: hPa		Rwy Elev: 397 hPa		Trans level: By ATC
DME required.		Trans alt: 18000'		



RECOMMENDED ALTITUDES	
LOC (GS out)	
DIST to THR	ALTITUDE
7.0	14950'
6.0	14700'
5.0	14440'
4.0	14190'
3.0	13930'
2.0	13680'



Gnd speed-Kts	70	90	100	120	140	160	ALS	PAZ	17000'
GS	2.40°	297	382	424	509	594	679	115.7 R-181	
MAP at VOR									

STRAIGHT-IN LANDING RWY 10				CIRCLE-TO-LAND			
ILS		LOC (GS out)		Max Kts		MDA(H)	
DA(H)	13331' (220')	MDA(H)	13550' (439')				
FULL	ALS out		ALS out				
A				100	14050' (736')	-2000m	
B	1200m	1600m	1600m	135	14050' (736')	-2400m	
C				180	14660' (1346')	-4000m	
D		2000m	2000m	205	15130' (1816')	-4400m	

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE


CHANGES: Procedure.

SLLP/LPB EL ALTO INTL

22 MAY 15 **(11-3)**

MISSED APCH CLIMB
GRADIENT MIM 3.0%

LA PAZ, BOLIVIA
ILS X Rwy 10



PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

SLLP/LPB EL ALTO INTL


22 MAY 15 **(11-4)**


MISSED APCH CLIMB
GRADIENT MIM 3.0%

LA PAZ, BOLIVIA
ILS W Rwy 10


BRIEFING STRIP™

15
10
5
0
5

LA PAZ Approach 119.5		LA PAZ Tower 118.3		Ground 121.9	
LOC ILPA 110.3	Final Apch Crs 099°	Minimum Alt D7.2 ILPA 15000' (1890')	ILS DA(H) 13330' (220')	Apt Elev 13314'	Rwy 13110'
MISSED APCH: Maintain heading 099° to D2.4 ILPA and climb to 13700'. Then turn RIGHT and intercept LPZ NDB R-182 direct to D35.0 LPZ and climb to 17000' to hold and request instructions from CONTROL.					
Alt Set: hPa		Rwy Elev: 397 hPa	Trans level: By ATC		Trans alt: 18000'
1. ADF and DME required. 2. Max IAS 200 Kts.					
					MSA LPZ NDB



LOC (GS out)	DIST to THR	6.0	5.0	4.0	3.0	2.0	1.0
	ALTITUDE	14860'	14610'	14350'	14100'	13840'	13590'



Gnd speed-Kts	70	90	100	120	140	160			
GS	2.40°	297	382	424	509	594	679		
MAP at D0.7 ILPA or D7.2 ILPA to MAP	6.5	5:34	4:20	3:54	3:15	2:47	2:26		
								ALS	13700'
								REIL PAPI	D2.4 ILPA

STRAIGHT-IN LANDING RWY 10					CIRCLE-TO-LAND			CIRCLING Not Authorized 
ILS		LOC (GS out)						
DA(H)	13330' (220')	MDA(H)		13420' (310')	Max Kts.	MDA(H)		
FULL	ALS out			ALS out	100	14100' (786') - 1900m		
A	800m	1600m	1600m	1600m	135	14100' (786') - 2800m		
B		2400m	2400m	2400m	180	14200' (886') - 3700m		
C			2400m	2400m	2400m	205	14200' (886') - 4600m	
D				2400m	2400m	2400m		

PANS OPS

CHANGES: Missed approach climb gradient.


PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

SLLP/LPB
EL ALTO INTL


14 JUN 19 (11-5)

LA PAZ, BOLIVIA
ILS V Rwy 10


LA PAZ Approach 119.5		LA PAZ Tower 118.3		Ground 121.9	
LOC ILPA 110.3	Final Aptch Crs 100°	Minimum Alt D7.2 ILPA 15000' (1889')	ILS DA(H) 13331' (220')	Apt Elev 13314' Rwy 13111'	
MISSED APCH: Turn RIGHT and intercept PAZ VOR R-181 outbound to D20.0 PAZ climbing to 17000' and hold. Request instructions from ATC.					
Alt Set: hPa		Rwy Elev: 397 hPa	Trans level: By ATC		Trans alt: 18000'
DME required.					



MSA PAZ VOR



DIST to THR	7.2	7.0	6.0	5.0	4.0	3.0	2.0
ALTITUDE	15000'	14950'	14700'	14440'	14190'	13930'	13680'



Gnd speed-Kts	70	90	100	120	140	160	ALS REIL PAPI	PAZ 115.7 R-181	17000	↑
Gs 2.40°	297	382	424	509	594	679				
MAP at VOR										

STRAIGHT-IN LANDING RWY10					CIRCLE-TO-LAND	
ILS			LOC (GS out)			
DA(H) 13331' (220')			MDA(H) 13550' (439')			
FULL			ALS out		Max Kts	MDA(H)
A	1200m	1600m	1600m	100	14050'	(736') -2000m
B				135	14050'	(736') -2400m
C				180	14660'	(1346') -4000m
D		205	15130'	(1816') -4400m		
		2000m	2000m			

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

PANS OPS

CHANGES: Reissue.

SLLP/LPB
EL ALTO INTL

4 OCT 19
Eff 10 Oct


12-1

MISSED APCH CLIMB
GRADIENT MIM 3.0%


LA PAZ, BOLIVIA
RNAV(GNSS) Z Rwy 10

BRIEFING STRIP™

LA PAZ Approach 119.5		LA PAZ Tower 118.3		Ground 121.9	
RNAV	Final Apch Crs 100°	LP625 MANDATORY 14800' (1689')	LNAV MDA(H) 13490' (379')	Apt Elev 13314'	TAA 25 NM IAF
				Rwy 13111'	
MISSED APCH: RIGHT turn climb to 17000' to LP627, enter hold and request instructions from ATC.					
Missed approach requires a minimum climb gradient of 3.0%.					
NM to LP627		5.0	10.0	15.0	20.0
3.0% Climb Gradient		14380'	15260'	16140'	17000'
Alt Set: hPa 1. GNSS required.		Rwy Elev: 397 hPa	Trans level: By ATC		Trans alt: 18000'



DIST to THR	5.0	4.0	3.0	2.0	1.0
ALTITUDE	14800'	14470'	14120'	13800'	13490'



Gnd speed-Kts	70	90	100	120	140	160	REIL PAPI	ALS	RT	182° hdg	17000'
Descent Angle 3.00°	372	478	531	637	743	849					
MAP at LP626 or FAF to MAP	4.0	3:26	2:40	2:24	2:00	1:43					

STRAIGHT-IN LANDING RWY 10				CIRCLE-TO-LAND			
LNAV MDA(H) 13490' (379')							
ALS out				Max Kts	MDA(H)		
A	1600m	2000m		100	14050'	(736')	-2000m
B				135	14050'	(736')	-2400m
C	2000m	2400m		180	14660'	(1346')	-4000m
D	2400m	2800m		205	15130'	(1816')	-4400m

PANS OPS

CHANGES: Text, altitudes, topography.

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

SLLP/LPB
EL ALTO INTL


4 OCT 19
Eff 10 Oct

12-2


MISSED APCH CLIMB
GRADIENT MIM 3.0%

LA PAZ, BOLIVIA
RNAV(GNSS) Y Rwy 10

LA PAZ Approach 119.5		LA PAZ Tower 118.3		Ground 121.9	
RNAV	Final ApcH Crs 100°	LP657 MANDATORY 14500'(1389')	LNNAV MDA(H) 13490'(379')	Apt Elev 13314' Rwy 13111'	TAA 25 NM IAF
MISSED APCH: Turn RIGHT climbing to 17000' DIRECT to LP627 and hold. Request ATC instructions. Missed approach requires a minimum climb gradient of 3.0%.					
Alt Set: hPa		Rwy Elev: 397 hPa		Trans level: By ATC	
GNSS required.		Trans alt: 18000'			



DIST to THR	5.2	4.0	3.0	2.0	1.0
ALTITUDE	14550'	14230'	13960'	13700'	13430'



Gnd speed-Kts	70	90	100	120	140	160	REIL PAPI	ALS 17000'	RT D	LP627
Descent Angle	2.50°	310	398	442	531	707				
MAP at RWY10										

STRAIGHT-IN LANDING RWY 10				CIRCLE-TO-LAND			
LNNAV MDA(H) 13490' (379')							
		ALS out		Max Kts	MDA(H)		
A	1600m	2000m		100	14050'	(736')	-2000m
B	2000m	2400m		135	14050'	(736')	-2800m
C	2000m	2400m		180	14660'	(1346')	-3700m
D	2400m	2800m		205	15130'	(1816')	-4600m

CHANGES: New procedure.

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE




SLLP/LPB
EL ALTO INTL

31 MAY 19 (13-1)

LA PAZ, BOLIVIA
VOR Z Rwy 10

BRIEFING STRIP™

LA PAZ Approach		LA PAZ Tower		Ground
119.5		118.3		121.9
VOR PAZ 115.7	Final Apch Crs 100°	Minimum Alt D4.6 15000' (1889')	MDA(H) 13570' (459')	Apt Elev 13314' Rwy 13111'
MISSED APCH: Turn RIGHT to intercept PAZ VOR R-181 outbound climbing to 17000' to D20.0 PAZ VOR, enter hold LEFT turns 001° and request instructions from ATC.				
Alt Set: hPa		Rwy Elev: 397 hPa		Trans level: By ATC
1. DME required. 2. MAX 160 KT. 3. PAPI angle not coincident.		Trans alt: 18000'		MSA PAZ VOR



Gnd speed-Kts	70	90	100	120	140	160	REIL	PAZ	17000'
Descent Angle	2.92°	362	465	517	620	723	826	115.7	
MAP at VOR or								R-181	
D4.6 to MAP	4.6	3:57	3:04	2:46	2:18	1:58	1:43		

STRAIGHT-IN LANDING RWY 10

CIRCLE-TO-LAND

MDA(H) 13570' (459')		Max Kts	MDA(H)
ALS out		100	14050' (736') -2000m
A		135	14050' (736') -2400m
B		180	14660' (1346') -4000m
C		205	15130' (1816') -4400m
D			

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE


PANS OPS

CHANGES: Procedure.

SLLP/LPB
EL ALTO INTL

31 MAY 19 (13-2)

LA PAZ, BOLIVIA
VOR Y Rwy 10






PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

SLLP/LPB EL ALTO INTL

11 JUN 10 (16-1)

LA PAZ, BOLIVIA
CAT B & C NDB Rwy 10

BRIEFING STRIP™	LA PAZ Approach 119.5		LA PAZ Tower 118.3		Ground 121.9		
	NDB LPZ 350	Final Apch Crs 091°	No FAF	MDA(H) 13900' (788')	Apt Elev 13313' RWY 10 13112'		
	MISSED APCH: Turn RIGHT and follow 173° heading climbing to 17000', request instructions from CONTROL .						
	Alt Set: hPa		Rwy Elev: 397 hPa	Trans level: By ATC			Trans alt: 18000'
	1. Max IAS 160 Kts.						
						MSA LPZ NDB	



Start turn at 2 Min 30 Sec 16000' to 15500'				NDB 18000' RWY 10 13112'	
MAP at NDB				REIL PAPI	173° hdg 17000'
STRAIGHT-IN LANDING RWY10 MDA(H) 13900' (788')				CIRCLE-TO-LAND	
ALS out				CIRCLING Not Authorized	
A NOT APPLICABLE				A NOT APPLICABLE	
B 1600m				B 135 13930' (617') - 2800m	
C 3600m				C 180 14100' (787') - 3700m	
D NOT APPLICABLE				D NOT APPLICABLE	

CHANGES: MSA.

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE


SLOR/ORU
Apt Elev 12164'
S17 57.3 W067 4.5

28 JUL 17

10-9

ORURO, BOLIVIA
JUAN MENDOZA

*ORURO Tower 118.5



PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

CHANGES: None.

PARA USO EN AVIACIÓN VIRTUAL UNICAMENTE


ADDITIONAL RUNWAY INFORMATION					
RWY		USABLE LENGTHS		TAKE-OFF	WIDTH
		LANDING BEYOND			
		Threshold	Glide Slope		
101	RL PAPI (angle 3.0°)	12,467' 3800m		NA	148' 45m
219	RL				
1 No departures Rwy 1 due to high tension power lines and towers. 2 No landing Rwy 19 in wind of 10 kts or greater, except wind from 180° due to high tension power lines and tower.					
TAKE-OFF					
	All Rwys				
1 & 2 Eng	1600m				
3 & 4 Eng	800m				

SLOR/ORU
JUAN MENDOZA

20 MAY 16
Eff 26 May (12-1)

CAT A, B & C

ORURO, BOLIVIA
RNAV (GNSS) Z Rwy 01



PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

SLOR/ORU

ORURO, BOLIVIA


VOR Z RWY 01

JUAN MENDOZA

28 AUG 15 (13-1)

CAT A, B & C

MISSED APCH CLIMB GRADIENT MIM 6%



PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

SLOR/ORU
JUAN MENDOZA


28 AUG 15 **13-2**


CAT A, B & C

ORURO, BOLIVIA
VOR Y RWY 01


MISSED APCH CLIMB GRADIENT MIN 6%

BRIEFING STRIP™

LA PAZ Control 128.2			*ORURO Tower 118.5		
VOR ORU 113.0	Final Apch Crs 010°	Minimum Alt D5.0 13900' (1754')	MDA(H) 12640' (494')	Apt Elev 12164' Rwy 12146'	 MSA ORU VOR
MISSED APCH: Maintain course 010° until crossing 15000', (6%). Turn LEFT onto heading 212° to intercept outbound ORU VOR R-257, climbing to 16000' maintain outbound ORU VOR R-257 to D20.0 ORU, enter hold at 077° left turn and request ATC instructions.					
Alt Set: INCHES Rwy Elev: 373 hPa Trans level: By ATC Trans alt: 18000' 1. DME Required. 2. Unlit power lines near Rwy 19 threshold.					



ORU DME	5.0	4.0	3.0	2.0
ALTITUDE	13900'	13585'	13270'	12955'



Gnd speed-Kts	70	90	100	120	140	160	PAPI	15000'	16000'	212° hdg
Descent Angle 3.00°	372	478	531	637	743	849				
MAP at D1.0										
D5.0 to MAP 4.0	3:26	2:40	2:24	2:00	1:43	1:30				

STRAIGHT-IN LANDING RWY 01				CIRCLE-TO-LAND			
MDA(H) 12640' (494')							
A	1600m			A			
B				B			
C	2000m			C	NOT APPLICABLE		
D	NOT APPLICABLE			D			

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE


PANS OPS

CHANGES: Missed approach procedure, recommended altitudes, frequency.

SLPO/POI
Apt Elev **12923'**
S19 32.5 W065 43.4

28 JUL 17 (10-9)

POTOSI, BOLIVIA
CAPT NICOLAS ROJAS




ADDITIONAL RUNWAY INFORMATION					
RWY		USABLE LENGTHS		TAKE-OFF	WIDTH
		LANDING BEYOND			
		Threshold	Glide Slope		
06	24				98' 30m
TAKE-OFF					
	All Rwy's				
1 & 2 Eng	1600m				
3 & 4 Eng	800m				


CHANGES: Take-off minimums, airport elevation.

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

LA PAZ Control				*POTOSI Tower	
128.2				118.3	
RNAV	Final Apch Crs 245°	Minimum Alt PO365 14600' (1822')	LNAV MDA(H) 13950' (1172')	Apt Elev 12922' Rwy 12778'	TAA 25 NM IAF
MISSED APCH: Climb direct to PO633 at or above 15300', 4.0 % climb gradient, turn LEFT climbing to 17000' and join holding 017°, RIGHT turns, and request ATC instructions.					
Alt Set: hPa Rwy Elev: 388 hPa Trans level: By ATC Trans alt: 18000' 1. GNSS required.					



DIST TO THR	4.0	5.0
ALTITUDE	14270'	14600'



Gnd speed-Kts	70	90	100	120	140	160	15300' ↑	➔	PO633
Descent Angle 3.38°	419	538	598	718	837	957			
MAP at RW24									
FAF to MAP	5.0	4:17	3:20	3:00	2:30	2:09			

STRAIGHT-IN LANDING RWY 24 Missed Apch Climb Gradient Mim 4.0% LNAV MDA(H) 13950' (1172')				CIRCLE-TO-LAND	
A	2400m			Max Kts	NOT APPLICABLE
B	2800m			A	
C	4800m			B	
D	NOT APPLICABLE			C	

SLPO/POI CAT A, B & C

CAPT NICOLAS ROJAS

9 SEP 16

12-2

MISSED APCH CLIMB
GRADIENT MIN 4.0%

POTOSI, BOLIVIA

RNAV (GNSS) Y Rwy 24

LA PAZ Control

*POTOSI Tower

128.2

118.3

RNAV

Final
Apch Crs

245°

Minimum Alt

PO645

15000' (2222')

LNAV

MDA(H)

13950' (1172')

Apt Elev 12922'

Rwy 12778'

TAA

25 NM

IAF

MISSED APCH: Climb direct to PO633 at or above 15300', 4.0 % climb gradient, turn LEFT climbing to 17000' and join holding 017°, RIGHT

Alt Set: hPa

Rwy Elev: 388 hPa

Trans level: By ATC

Trans alt: 18000'

1. GNSS required.

MISSED APCH FIX

PO633

15300

PO632

17000

PO645

PO643

(IF)

095°

18000

275°

PO641

(IAF)

13354'

19-30

14000

7.0

245°

13677'

14000

15000

16000

15595'

14000

15000

16000

16455'

14000

15000

16000

16455'

14000

15000

16000

16455'

14000

15000

16000

16455'

14000

15000

16000

16455'

14000

15000

16000

16455'

14000

15000

16000

16455'

14000

15000

16000

16455'

14000

15000

16000

16455'

14000

15000

16000

16455'

14000

15000

16000

16455'

DIST to THR

4.0

5.0

6.0

ALTITUDE

14270'

14650'

15000'

PO641

PO645

PO643

RW24

TCH 50'

Rwy 12778'

0

3.1

2.9

6.0

6.0

6.0

6.0

6.0

6.0

6.0

6.0

6.0

6.0

6.0

6.0

6.0

6.0

6.0

6.0

6.0

Gnd speed-Kts

70

90

100

120

140

160

Descent Angle

3.38°

419

538

598

718

837

957

MAP at RW24 or

FAF to MAP

6.0

5:09

4:00

3:36

3:00

2:34

2:15

CIRCLE-TO-LAND

STRAIGHT-IN LANDING RWY 24
Missed Apch Climb Gradient Min 4.0%

LNAV

MDA(H)

13950' (1172')

Max

Kts

A

2400m

A

B

2800m

B

C

4800m

C

D

NOT APPLICABLE

D

NOT APPLICABLE

CHANGES: New procedure.

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

SLPO/POI CAT A, B & C

CAPT NICOLAS ROJAS


4 OCT 19

(13-1)

Missed Apch Climb
Gradient Mim 3.3%

POTOSI, BOLIVIA

VOR Z Rwy 24



PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

SLPS/PSZ
TTE AV SALVADOR OGAYA G

10-2


15 JUN 18
Eff 21 Jun

PUERTO SUAREZ, BOLIVIA


ARRIVAL

Apt Elev
440'

Alt Set: hPa Trans level: By ATC Trans alt: 4000'



ARRIVALS



PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE


CHANGES: Airway UA-304 removed, airport name.

SLPS/PSZ
Apt Elev 440'
S18 58.8 W057 49.4

28 JUL 17

12-1


PUERTO SUAREZ, BOLIVIA
TTE AV SALVADOR OGAYA G



PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

ADDITIONAL RUNWAY INFORMATION					
RWY		USABLE LENGTHS			
		LANDING BEYOND		TAKE-OFF	WIDTH
		Threshold	Glide Slope		
05	23	RL PAPI-L			118' 36m
TAKE-OFF					
	All Rwys				
1 & 2 Eng	1600m				
3 & 4 Eng	800m				

CHANGES: Take-off minimums, airport name.



PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

TTE AV SALVADOR OGAYA INTL

10 DEC 10

16-1

NDB-1 Rwy 23

BRIEFING STRIP TM


NDB
PSZ
***290**

Final
Apch Crs
218°

No FAF

MDA(H)
(CONDITIONAL)
840' (466')

Apt Elev 440'
Rwy 23 **374'**



MISSED APCH: Climb on the 250° bearing from PSZ NDB until reaching 3000' and request instructions from CONTROL.


Alt Set: hPa

Rwy Elev: 14 hPa

Trans level: By ATC

Trans alt: 4000'

MSA PSZ NDB



Start turn at
CAT A & B 2½ Min
CAT C & D 2 Min
or within
6 NM
3000'
to
2500'

RWY 23 **374'**

							PAPI-L	3000' PSZ on *290 250°
<i>MAP at NDB</i>								

STRAIGHT-IN LANDING RWY23

CIRCLE-TO-LAND

MDA(H) **840'** (466')

DAY

NIGHT

Not Authorized East of Airport

Max Kts	100
	135
	180
	205

 $MDA(H)$

1030' (590') - 2.4 km

1130' (690') -3.6 km

CHANGES: Airport elevation, printing sequence.

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

PANS OPS 3

*PUERTO SUAREZ Tower 118.5



NDB CUB 375	Final Apch Crs 295°	No FAF	MDA(H) Refer to Minimums	Apt Elev 440'
-------------------	---------------------------	--------	--------------------------------	---------------

MISSED APCH: Turn RIGHT climbing to 4000' and proceed to CUB NDB. Request instructions from CONTROL.

Alt Set: hPa Apt Elev: 16 hPa Trans level: By ATC Trans alt: 4000'

1. This procedure is usable when PSZ NDB is out of service and previous coordination between Corumba Approach and Puerto Suarez Tower has been made.

MSA CUB NDB




0							8.0					
Gnd speed-Kts		70	90	100	120	140	160	Lighting - Refer to Airport Chart	4000' 	CUB 375		
NDB to MAP		8.0	6:51	5:20	4:48	4:00	3:26	3:00				
STRAIGHT-IN LANDING								CIRCLE-TO-LAND				
A B C D								DAY		NIGHT		
								Max Kts	MDA(H)		1030' (590') - 2.4 km	NA
								100				
								135				
								180				
								205	1130' (690') - 3.6 km			

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

SLRI/RIB
Apt Elev **463'**
S11 00.6 W066 04.4

4 OCT 19 (10-9)

RIBERALTA, BOLIVIA
CAP DE AV SELIN ZEITUN LOPEZ



ADDITIONAL RUNWAY INFORMATION

RWY		USABLE LENGTHS		TAKE-OFF	WIDTH
		LANDING BEYOND Threshold	Glide Slope		
14	32				69' 21m

TAKE-OFF

	All Rwys
1 & 2 Eng	1600m
3 & 4 Eng	800m


PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

CHANGES: Airport coordinates, communications, NDB removed, rwy length.

SLRQ/RBQ
Apt Elev **666'**
S14 25.6 W067 29.9

28 JUL 17 **10-9**

RURRENABAQUE, BOLIVIA
RURRENABAQUE



14

144

Elev 644'

ARP

4921' 1500m

NDB

32

324

Elev 666'

Rwy 14/32 restricted for aircraft weighing more than 55,000 lbs.
Rwy 32 right traffic pattern.

069°N

Feet 0 500 1000 1500 2000 2500
Meters 0 200 400 600 800

ADDITIONAL RUNWAY INFORMATION					
RWY		USABLE LENGTHS		TAKE-OFF	WIDTH
		Threshold	Landing Beyond Glide Slope		
14					98'
32					30m
TAKE-OFF					
	All Rwys				
1 & 2 Eng	1600m				
3 & 4 Eng	800m				

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

CHANGES: Runway elevation, magnetic variation, take-off minimums.

SLRQ/RBQ

MISSED APCH CLIMB
GRADIENT MIM 4.6%

RURRENABAQUE, BOLIVIA

RURRENABAQUE

24 MAR 17
Eff 30 Mar


(12-1)

CAT A, B & C


RNAV (GNSS) Y Rwy 14

BRIEFING STRIP™

LA PAZ Control 128.2		*RURRENABAQUE Approach 118.1		*RURRENABAQUE Tower 118.1	
RNAV	Final Apch Crs 145°	Minimum Alt REDUT 2400' (1755')	LNAV MDA(H) 1300' (655')	Apt Elev 666' Rwy 645'	TAA 25 NM IAF
MISSED APCH: Climbing LEFT turn to 4000' direct to KIDAR, enter hold 283° right turns and request ATC instructions.					
		GS (KT)/FT/MIN 4.6% Climb Gradient	90 110 120 130 140 150 160 420' 515' 560' 610' 655' 700' 745'		
Alt set: hPa Rwy Elev: 23 hPa Trans level: By ATC Trans alt: 6000'					
1. GNSS required. 2. MAX 160 KT. 3. CAUTION: High voltage tower 0.8 NM southeast of the threshold Rwy 32 at 960'.					



DIST to THR	5.2	4.0	3.0	2.0	1.8
ALTITUDE	2400'	1970'	1650'	1330'	1300'



Gnd speed-Kts	70	90	100	120	140	160
Descent Angle 3.00°	372	478	531	637	743	849
MAP at UTLAS or REDUT to MAP	4.4	3:46	2:56	2:38	2:12	1:53

STRAIGHT-IN LANDING RWY 14 MISSED APCH CLIMB GRADIENT MIM 4.6%		CIRCLE-TO-LAND MISSED APCH CLIMB GRADIENT MIM 4.6%	
LNAV MDA(H) 1300' (655')		Visual Circling only North of Rwy 14/32	
A	1600m	Max Kts 100	1300' (634') - 1900m
B		135	1800' (1134') - 1900m
C	2000m	180	2300' (1634') - 2500m
D	NOT APPLICABLE	D	NOT APPLICABLE

PANS OPS


CHANGES: New procedure.

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

Apt Elev **407'**
S16 20.4 W058 24.1

(12-1)

SAN MATIAS, BOLIVIA
SAN MATIAS



ADDITIONAL RUNWAY INFORMATION				
RWY		USABLE LENGTHS		
		Threshold	Landing Beyond Glide Slope	Take-Off
03	21			98' 30m
TAKE-OFF				
	All Rwy's			
1 & 2 Eng	1600m			
3 & 4 Eng	800m			

CHANGES: Take-off minimums.

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

SLTI
SAN MATIAS

28 JUL 17

(12-1)

CAT A & B

SAN MATIAS, BOLIVIA
RNAV (GNSS) Z Rwy 03

PUERTO SUAREZ Center
128.2

*SAN MATIAS Tower
118.3


RNAV

Final
Apch Crs
027°

Minimum Alt
SANGA
2500' (2107')


LNAV
MDA(H)
(CONDITIONAL)
900' (507')

Apt Elev **407'**
Rwy 03 **393'**



MISSED APCH: Proceed to LOGIN, turn LEFT onto heading 254° to PAPIT climbing to 3000', join hold and request ATC instructions. No turns are authorized before MAP.

Alt Set: hPa Rwy Elev: 14 hPa Trans level: By ATC Trans alt: 4000'
1. Obstruction (antenna) at 0.36 NM after MAP and 0.12 NM to the right of approach course.



DISTANCE to MAP

3.8

3.0

2.0

1.0

0.0

ALTITUDE

2500'

2050'

1670'

1280'

900'

REDES

SANGA

GAXET

2500'

2500'

[3.59°]

[TCH 50']

Rwy 03 **393'**

Gnd speed-Kts

70

90

100

120

140

160

Descent angle [3.59°]

445

572

635

762

889

1017

MAP at GAXET or

SANGA to MAP

3.8

3:15

2:32

2:17

1:54

1:38

1:26

LOGIN

3000'

LT

254°

PAPIT

1 STRAIGHT-IN LANDING RWY 03

LNAV

MDA(H) **900'** (507')

1 CIRCLE-TO-LAND

Max
Kts

100

135

MDA(H)

1400' (993') -2800m

A

2300m

C

NOT APPLICABLE

D

NOT APPLICABLE

D

1 Night NA.

CHANGES: None.


PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

TARIJA, BOLIVIA 

24 AUG 18


SID

Trans level: By ATC Trans alt: 18000'
DME required.



KOTKI 1 [KOTKI1], PULSA 1 [PULSA1]
SINIT 1 [SINIT1]
DEPARTURES
(RWY 13)

SPEED: MAX 175 KT



These SIDs require minimum climb gradients:
KOTKI 1, PULSA 1: 5.5% until D6.0 TAR.
SINIT 1: 5.5% until D6.0 TAR. 4.2% until SINIT.

Gnd speed-KT	75	100	150	200	250	300
4.2% V/V (fpm)	319	425	638	851	1063	1276
5.5% V/V (fpm)	418	557	835	1114	1392	1671

INITIAL CLIMB

After takeoff, MAINTAIN runway heading until D6.0 TAR climbing to 7600' or above, turn RIGHT and intercept TAR R-175. cross TAR VOR at or above 11800'.

SID	ROUTING
KOTKI 1	A† TAR VOR, TAR R-359 to KOTKI, cross KOTKI at or above FL170.
PULSA 1	A† TAR VOR, TAR R-032 to PULSA, cross PULSA at or above FL170.
SINIT 1	A† TAR VOR, TAR R-336 to SINIT, continue climb and cross SINIT at or above FL190.


CHANGES: Airport name.

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

SLTJ/TJA
Apt Elev **6096'**
S21 33.1 W064 42.5

24 AUG 18 **(10-9)**

TARIJA, BOLIVIA
CAPT AV. ORIEL LEA PLAZA



ADDITIONAL RUNWAY INFORMATION

RWY		USABLE LENGTHS		TAKE-OFF	WIDTH
		LANDING	BEYOND		
		Threshold	Glide Slope		
13	HIRL PAPI-L (angle 3.00°)	8793' (2680m)		8793' (2680m)	148' 45m
31	HIRL PAPI-L (angle 3.00°)				

TAKE-OFF

	All Rwys
1 & 2 Eng	1600m
3 & 4 Eng	800m

CHANGES: Airport name, lighting, magnetic variation.

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

SLTJ/TJA

MISSED APCH CLIMB
GRADIENT MIM 4.7%


CAPT AV. ORIEL LEA PLAZA

24 AUG 18 (13-1)

CAT B & C

TARIJA, BOLIVIA

VOR B Rwy 13



PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

VOR C Rwy 13


STRAIGHT-IN LANDING RWY 13 Missed apch climb gradient mim 4.7% MDA(H) 6950' (855')		CIRCLE-TO-LAND Missed apch climb gradient mim 4.7% MDA(H) _____	
A	NA	A	NA
B	2000m	135	7600' (1505') -2800m
C	2200m	180	7900' (1805') -3700m
D	NA	D	NA

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

PANS OPS

CHANGES: Airport name.

ARRIVALS




CHANGES: Airway W-4 removed.

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

Apt Elev 509'	Trans level: By ATC Trans alt: 5000' TRI VOR/DME required.
------------------	--

AKRIM 1 [AKRIM1], MOXUS 1 [MOXUS1] DEPARTURES




These SIDs require a minimum climb gradient:
Rwy 14: 5.8% to 1200'.

Gnd speed-KT	75	100	150	200	250	300
5.8% V/V (fpm)	441	587	881	1175	1468	1762

RWY	INITIAL CLIMB
14	After take-off MAINTAIN runway heading to at or above 1200', turn RIGHT course 345° and intercept TRI R-300 to DALNO.
32	After take-off MAINTAIN runway heading to at or above 1100', turn LEFT and intercept TRI R-300 to DALNO.
SID	ROUTING
AKRIM 1 (T-521)	From DALNO track 341° to AKRIM.
MOXUS 1	From DALNO track 259° to MOXUS.

CHANGES: Airway W-4 removed.

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE



TRINIDAD, BOLIVIA


SID

Trans level: By ATC Trans alt: 5000'
TRI VOR/DME required.



2000'

MSA TRI VOR



These SIDs require a minimum climb gradient:
Rwy 14: 5.8% to 1200'.


Gnd speed-KT	75	100	150	200	250	300
5.8% V/V (fpm)	441	587	881	1175	1468	1762

RWY	INITIAL CLIMB	
14	After take-off MAINTAIN runway heading to at or above 1200', turn RIGHT course 277° and intercept TRI R-232 to KEXOT.	
32	After take-off MAINTAIN runway heading to at or above 1100', turn LEFT course 202° and intercept TRI R-232 to KEXOT.	
SID		ROUTING
EKAVI 2 (UW-12, W-12)		From KEXOT track 193° to EKAVI.
IRIVA 1 (UW-568, W-9)		From KEXOT track 270° to IRIVA.

CHANGES: None.


PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

Apt Elev 509'	Trans level: By ATC Trans alt: 5000' TRI VOR/DME required.
------------------	--



RWY	INITIAL CLIMB
14	After take-off MAINTAIN runway heading to at or above 1200', turn LEFT course 292° and intercept TRI R-322 to NAXAS.
32	After take-off MAINTAIN runway heading to TRI, intercept TRI R-322 to NAXAS.
SID	ROUTING
KETIP 1 (A-301)	From NAXAS track 003° to KETIP.
TOBLI 1 (W-12)	From NAXAS track 013° to TOBLI.

Apt Elev 509'	Trans level: By ATC Trans alt: 5000' TRI VOR/DME required.
------------------	--




RWY	INITIAL CLIMB
14	After take-off MAINTAIN runway heading to at or above 1200', turn LEFT course 355° and intercept TRI R-025 to SARPA.
32	After take-off MAINTAIN runway heading to at or above 1100', turn RIGHT course 055° and intercept TRI R-025 to SARPA.
SID	ROUTING
MIKAL 1 (T-510)	From SARPA track 330° to MIKAL.
UBLEX 1 (M-653)	From SARPA track 347° to UBLEX.

Apt Elev **509'**
S14 49.2 W064 55.1

14 JUL 17 (10-9)

TRINIDAD, BOLIVIA
JORGE HENRICH




ADDITIONAL RUNWAY INFORMATION					
RWY		USABLE LENGTHS		TAKE-OFF	WIDTH
		Threshold	Glide Slope		
14	HIRL PAPI-L (angle 3.00°)				98' 30m
32					
	TAKE-OFF				
	All Rwys				
1 & 2 Eng	1600m				
3 & 4 Eng	800m				


CHANGES: Airport name, take-off minimums.

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

*TRINIDAD Approach		*TRINIDAD Tower		*Ground	
119.1		118.5		121.9	
RNAV	Final Apch Crs 145°	Minimum Alt GELOP 2200' (1692')	LNAV MDA(H) 800' (292')	Apt Elev 508' Rwy 14 508'	2000' MSA ARP
MISSED APCH: Turn LEFT on heading 086° direct to LIVOS climbing to 4000' and join holding. Request ATC instructions.					
Alt Set: hPa		Rwy Elev: 18 hPa	Trans level: By ATC	Trans alt: 5000'	



DIST TO THR	5.0	4.0	3.0	2.0	0.8
ALTITUDE	2200'	1840'	1520'	1200'	800'



Gnd speed-Kts	70	90	100	120	140	160	PAPI-L	4000' on LT	086° hdg	D	LIVOS
Descent angle [3.00°]	372	478	531	637	743	849					
MAP at RW14											
FAF to MAP	5.0	4:17	3:20	3:00	2:30	2:09					

STRAIGHT-IN LANDING RWY 14			CIRCLE-TO-LAND		
LNAV					
MDA(H) 800' (292')			Max Kts	MDA(H)	
A	1600m		100	1200' (692') - 1900m	
B			135	1300' (792') - 1900m	
C	2000m		180	1400' (892') - 2300m	
D	NA		D	NA	

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

SLTR/TDD
JORGE HENRICH INTL



8 APR 16 (13-1)

TRINIDAD, BOLIVIA
VOR DME-2 Rwy 14

BRIEFING STRIP

TM

*TRINIDAD Approach		*TRINIDAD Tower		*Ground	
119.1		118.5		121.9	
VOR TRI 115.9	Final Apch Crs 143°	Minimum Alt D4.0 2100'(1592')	MDA(H) 870'(362')	Apt Elev 508' Rwy 14 508'	2000' MSA TRI VOR
MISSED APCH: Climb to 4000' outbound on TRI VOR R-143 and request instructions from CONTROL.					
Alt Set: hPa Rwy Elev: 18 hPa Trans level: By ATC Trans alt: 5000'					
1. Night operations on request. 2. MAX 200 KT.					



Gnd speed-Kts	70	90	100	120	140	160			PAPI-L	4000'	TRI
Descent Angle 3.00°	372	478	531	637	743	849				↑	on 115.9
											R-143
MAP at VOR											

STRAIGHT-IN LANDING RWY14				CIRCLE-TO-LAND			
MDA(H) 870' (362')				Max Kts	MDA(H)		
A				100	1010' (502') - 1900m		
B	1600m			135	1010' (502') - 2800m		
C				180	1110' (602') - 3700m		
D	2400m			205	1110' (602') - 4600m		

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE


CHANGES: TDD NDB removed, CNFs and VNAV info added, visibilities.

TRINIDAD, BOLIVIA
VOR 1 Rwy 14

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

STRAIGHT-IN LANDING RWY 14		CIRCLE-TO-LAND	
MDA(H) 1000' (491')		Max Kts	MDA(H) _____
A	1600m	100	1290' (781') -1900m
B		135	1290' (781') -2800m
C		180	1400' (891') -3700m
D		205	1400' (891') -4600m

CHANGES: TDD NDB removed, CNFs and VNAV info added, visibilities.



ADDITIONAL RUNWAY INFORMATION					
RWY			USABLE LENGTHS		WIDTH
			LANDING BEYOND	TAKE-OFF	
			Threshold	Glide Slope	
13					148'
31	RL	PAPI-L (angle 3.0°)			45m
TAKE-OFF					
	All Rwys				
1 & 2					
Eng	1600m				
3 & 4					
Eng	800m				

CHANGES: Take-off minimums.


PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE


SLUY
LA JOYA ANDINA

28 AUG 15 **13-1**


UYUNI, BOLIVIA
VOR Y Rwy 31

BREFFING STRIP™

LA PAZ Control 128.2				*LA JOYA ANDINA Tower 118.6	
VOR UNI 116.0	Final Apch Crs 308°	Minimum Alt D8.0 14700' (2676')	MDA(H) 12530' (506')	Apt Elev 12024' Rwy 12024'	
MISSED APCH: Continue to UNI VOR, turn LEFT to intercept outbound UNI VOR R-200, climbing to 16000' to D25.0 UNI VOR, join hold and request ATC instructions.					MSA UNI VOR
Alt Set: INCHES 1. DME required.	Rwy Elev: 370 hPa	Trans level: By ATC	Trans alt: 18000'		



UNI DME	1.1	2.0	3.0	4.0	5.0
ALTITUDE	12530'	12810'	13125'	13440'	13755'



Gnd speed-Kts	70	90	100	120	140	160	PAPI-L	16000' ↑	UNI 116.0		UNI 116.0 R-200
Descent Angle	3.00°	372	478	531	637	743					
MAP at D1.1 or FAF to MAP	6.9	5:55	4:36	4:08	3:27	2:57					

STRAIGHT-IN LANDING RWY 31

CIRCLE-TO-LAND

MDA(H) 12530' (506')						Max Kts	MDA(H)
A	1600m					100	12890' (866') -1900m
B						135	12900' (876') -2800m
C	2000m					180	13100' (1076') -3700m
D	2400m					205	13200' (1176') -4600m

PANS OPS


CHANGES: Procedure revised.

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

SLUY
LA JOYA ANDINA


28 AUG 15 (13-2)


UYUNI, BOLIVIA
VOR Z Rwy 31



PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

ARRIVALS







RWY	INITIAL CLIMB
16	After take-off intercept VIR R-163 to PULKO.
34	After take-off MAINTAIN runway heading climbing to 2500', turn RIGHT to intercept VIR R-163 to PULKO.
SID	ROUTING
ANBUN 1	From PULKO course 221° to ANBUN.
IRESU 1 (UL-322)	From PULKO course 231° to IRESU.
KABOM 1 (UL-404)	From PULKO course 206° to KABOM.
LIVON 1 (T-554)	From PULKO course 218° to LIVON.
LODAK 1 (W-8, UW-316)	From PULKO course 236° to LODAK.

Apt Elev
1224'

Trans level: By ATC Trans alt: 5000'



DIBAS 1 [DIBAS1], PAKES 1 [PAKES1]
SALBI 1 [SALBI1] DEPARTURES
(RWYS 16, 34)



INITIAL CLIMB	
SID	ROUTING
DIBAS 1 (UM-415)	From ISPER course 288° to DIBAS. Cross DIBAS at or above FL250.
PAKES 1 (A-301, UA-301)	From ISPER course 352° to PAKES. Cross PAKES at or above FL050.
SALBI 1 (A-304)	From ISPER course 281° to SALBI. Cross SALBI at or above FL230.

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

SLVR/VVI
VIRU VIRU INTL

20-3B

Eff 11 Oct




SANTA CRUZ, BOLIVIA

SID

Apt Elev
1224'

Trans level: By ATC Trans alt: 5000'

EIKO 1 [EIKO01], KOSBO 1 [KOSBO1]
SANSO 1 [SANSO1] RWYS 16, 34 DEPARTURES




INITIAL CLIMB	
After take-off MAINTAIN runway heading climbing to 2500', turn LEFT to intercept VIR R-264 VUOK.	
SID	ROUTING
EKIKO 1 (UL-797) KOSBO 1 (T-712, UT-712) SANSO 1 (W-11, UM-793, UW-677)	From VUOK course 234° to EKIKO. From VUOK course 290° to KOSBO. From VUOK course 298° to SANSO.

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE


CHANGES: Airway W-3 removed.

Apt Elev
1224'

Trans level: By ATC Trans alt: 5000'



GAVOS 1 [GAVOS1], SIKIN 1 [SIKIN1]
TOMUR 1 [TOMUR1] DEPARTURES



RWY	INITIAL CLIMB
16	After take-off MAINTAIN runway heading climbing to 2500', turn LEFT to intercept VIR R-134 to PALAG.
34	After take-off MAINTAIN runway heading climbing to 2500', turn RIGHT to intercept VIR R-134 to PALAG.
ROUTING	
GAVOS 1 (T-543)	From PALAG course 103° to GAVOS. Cross GAVOS at or above FL070.
SIKIN 1 (A-304)	From PALAG course 099° to SIKIN. Cross SIKIN at or above FL070.
TOMUR 1 (UM-415)	From PALAG course 117° to TOMUR. Cross TOMUR at or above FL250.

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

Apt Elev
1224'

Trans level: By ATC Trans alt: 5000'

PORGO 2 [PORGO2], SURKO 1 [SURKO1]
DEPARTURES

At or above
2500'

VIRU VIRU
D 113.8 VIR

517 37.6 W063 08.9

At or above
FL250

SURKO

At or above
FL250

At or above
FL050

PORGO

At or above
FL050

PULKO

At or above
FL050

5000'

090°

8000'

360°

MSA VIR VOR

N

NOT TO SCALE

PARA USO EN AVIACIÓN VIRTUAL UNICAMENTE


RWY	INITIAL CLIMB	
16	After take-off intercept VIR R-163 to PULKO.	
34	After take-off MAINTAIN runway heading climbing to 2500', turn RIGHT to intercept VIR R-163 to PULKO.	
SID		ROUTING
PORGO 2		From PULKO course 163° to PORGO.
SURKO 1		From PULKO course 152° to SURKO.

CHANGES: Airway A-556 revised.

SLVR/VVI
Apt Elev **1224'**
S17 38.8 W063 08.3

4 OCT 19 (20-9)

SANTA CRUZ, BOLIVIA
VIRU VIRU INTL



ADDITIONAL RUNWAY INFORMATION

				USABLE LENGTHS		TAKE-OFF	WIDTH
				LANDING BEYOND			
RWY				Threshold	Glide Slope		
16	HIRL SALS	PAPI-L (angle 3.0°)	RVR				148'
34	HIRL HIALS	PAPI-L (angle 3.0°)	RVR		10395' 3168m		45m

TAKE-OFF

All Rwys

1 & 2
Eng 1600m

3 & 4
Eng 800m

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

CHANGES: Twy E1, parking spots.



SLVR/VVI
VIRU VIRU INTL

1 JUN 18 (21-1)


SANTA CRUZ, BOLIVIA
ILS V Rwy 34

BRIEFING STRIP™

VIRU VIRU Approach 119.7		VIRU VIRU Tower 118.6		Ground 121.9	
LOC ILVV 110.9	Final Apch Crs 339°	GS D5.4 ILVV 3000' (1776')	ILS DA(H) 1454' (230')	Apt Elev 1224' Rwy 1224'	
MISSED APCH: Climb to 4000' heading 339° to VIR VOR, RIGHT turn direct to GUTOG/D15.0 VIR VOR, enter hold, 189° inbound, LEFT turns, and request instructions from ATC.					
Alt Set: hPa Rwy Elev: 44 hPa Trans level: By ATC Trans alt: 5000'					
1. DME required.					MSA VIR VOR



LOC (GS out)	ILVV DME ALTITUDE	1.0	2.0	3.0	4.0	5.4
		1592'	1911'	2229'	2548'	3000'



Gnd speed-Kts	70	90	100	120	140	160				
GS	3.12°	386	497	552	662	773	883			
MAP at D0.6 ILVV or FAF to MAP	4.8	4:07	3:12	2:53	2:24	2:03	1:48			



STRAIGHT-IN LANDING RWY34				CIRCLE-TO-LAND			
ILS DA(H) 1454' (230')		LOC (GS out) MDA(H) 1600' (376')		Max Kts		MDA(H)	
FULL	ALS out		ALS out				
A				100		1650' (426')	-2000m
B				135		1700' (476')	-2000m
C	800m	1600m		180		1800' (576')	-2800m
D				205		1900' (676')	-4000m

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

CHANGES: Reindexed, MSA flight level.

SLVR/VVI
VIRU VIRU INTL

1 JUN 18 (21-2)

SANTA CRUZ, BOLIVIA
ILS U Rwy 34

BRIEFING STRIP™

10

5



17-40

5


PANS OPS

VIRU VIRU Approach		VIRU VIRU Tower		Ground	
119.7		118.6		121.9	
LOC ILVV 110.9	Final Apch Crs 339°	GS D5.4 ILVV 3000' (1776')	ILS DA(H) 1454' (230')	Apt Elev 1224' Rwy 1224'	
MISSED APCH: Climb to 4000' heading 339° to VIR VOR, RIGHT turn direct to GUTOG/D15.0 VIR VOR, enter hold, 189° inbound, LEFT turns, and request instructions from ATC.					
Alt Set: hPa		Rwy Elev: 44 hPa		Trans level: By ATC	
1. DME required.				Trans alt: 5000'	

MSA VIR VOR



LOC (GS out)	ILVV DME	1.0	2.0	3.0	4.0	5.4
	ALTITUDE	1592'	1911'	2229'	2548'	3000'



Gnd speed-Kts	70	90	100	120	140	160	PAPI	4000'	339° hdg	VIR 113.8
GS	3.12°	386	497	552	662	773				
MAP at D0.6 ILVV or										
FAF to MAP	4.8	4:07	3:12	2:53	2:24	2:03				

STRAIGHT-IN LANDING RWY34				CIRCLE-TO-LAND	
ILS		LOC (GS out)		Max Kts	MDA(H)
DA(H)	1454' (230')	MDA(H)	1600' (376')		
FULL	ALS out		ALS out	100	1650' (426') -2000m
A				135	1700' (476') -2000m
B	800m	1600m	1200m	180	1800' (576') -2800m
C				205	1900' (676') -4000m
D			1600m		

CHANGES: Reindexed, MSA flight level.

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE


SLVR/VVI
VIRU VIRU INTL

16 SEP 11
Eff 22 Sep (22-1)


SANTA CRUZ, BOLIVIA
RNAV (GNSS) Z Rwy 16

BRIEFING STRIP™

VIRU VIRU Approach 119.7		VIRU VIRU Tower 118.6		Ground 121.9	
RNAV	Final Apch Crs 158°	Minimum Alt PULEK 2900' (1684')	LNAV MDA(H) 1500' (284')	Apt Elev 1224' Rwy 16 1216'	
MISSED APCH: Climb to 4000' direct to KIDEL, turn LEFT direct SELVI to holding 339° and request ATC instructions. No turns at the MAP.					
Alt Set: hPa	Rwy Elev: 44 hPa	Trans level: By ATC		Trans alt: 5000'	



DIST TO THR	5.0	4.0	3.0	2.0	0.7
ALTITUDE	2900'	2540'	2220'	1900'	1500'



Gnd speed-Kts	70	90	100	120	140	160			
Descent Angle [3.00°]	372	478	531	637	743	849			
MAP at RW16									
PULEK to MAP	5.0	4:17	3:20	3:00	2:30	2:09	1:53		

STRAIGHT-IN LANDING RWY16						CIRCLE-TO-LAND			
LNAV MDA(H) 1500' (284')									
ALS out						Max Kts			
A						100	1600' (376') - 1600m		
B	800m					135	1700' (476') - 1600m		
C						180	1800' (576') - 2400m		
D	1600m					205	1900' (676') - 3600m		

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

PANS OPS 4

CHANGES: Missed approach, minimums, recommended altitude band.


SLVR/VVI
VIRU VIRU INTL

29 JUN 18 (22-2)


SANTA CRUZ, BOLIVIA
RNAV (GNSS) Y Rwy 34

BRIEFING STRIP™

VIRU VIRU Approach 119.7		VIRU VIRU Tower 118.6		Ground 121.9	
RNAV	Final Apch Crs 339°	Minimum Alt AKROX 2900' (1676')	LNAV/VNAV DA(H) 1540' (316')	Apt Elev 1224' Rwy 1224'	TAA 25 NM IAF
MISSED APCH: Climb to 4000' direct VIR VOR, then turn RIGHT direct to GUTOG/D15.0 VIR VOR, enter holding and request instructions from ATC.					
Alt Set: hPa	Rwy Elev: 44 hPa	Trans level: By ATC	Trans alt: 5000'		
1. GNSS required. 2. Baro-VNAV procedure not authorized below 0°C (32°F) or above 35°C (95°F).					



DIST to DA(H)	1.0	2.0	3.0	4.0
ALTITUDE	1860'	2180'	2495'	2815'



Gnd speed-Kts	70	90	100	120	140	160	HIALS	4000'	D	VIR 113.8
Descent Angle	3.00°	372	478	531	637	743	849			
LNAV/VNAV: MAP at DA or FAF to MAP	4.2	3:36	2:48	2:31	2:06	1:48	1:35			
LNAV: MAP at RW34										

STRAIGHT-IN LANDING RWY 34				CIRCLE-TO-LAND			
LNAV/VNAV							
DA(H) 1540' (316')							
ALS out				Max Kts	MDA(H)	VIS	ALS out
A				100	1640' (416')	1600m	2000m
B	800m		1200m	135	1720' (496')		
C				180	1820' (596')	2400m	2800m
D	1600m		2000m	205	1920' (696')	3600m	4000m

CHANGES: None.

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE


SLVR/VVI
VIRU VIRU INTL

29 JUN 18 (22-3)


SANTA CRUZ, BOLIVIA
RNAV (GNSS) Z Rwy 34

BRIEFING STRIP™

VIRU VIRU Approach 119.7		VIRU VIRU Tower 118.6		Ground 121.9											
RNAV	Final Apch Crs 339°	Minimum Alt AKROX 2900' (1676')	LNAV MDA(H) 1600' (376')	Apt Elev 1224' Rwy 1224'	TAA 25 NM IAF										
MISSED APCH: Turn RIGHT, climb to 4000' direct to GUTOG, then enter LEFT turn holding 189° and request instructions from ATC.															
<table><tr><td>DIST to GUTOG</td><td>4.0</td><td>8.0</td><td>12.0</td><td>17.0</td></tr><tr><td>2.5% Climb Gradient</td><td>2200'</td><td>2800'</td><td>3400'</td><td>4000'</td></tr></table>						DIST to GUTOG	4.0	8.0	12.0	17.0	2.5% Climb Gradient	2200'	2800'	3400'	4000'
DIST to GUTOG	4.0	8.0	12.0	17.0											
2.5% Climb Gradient	2200'	2800'	3400'	4000'											
Alt Set: hPa	Rwy Elev: 44 hPa	Trans level: By ATC		Trans alt: 5000'											
1. GNSS required.															



DIST to THR	1.0	2.0	3.0	4.0	5.0
ALTITUDE	1600'	1920'	2230'	2580'	2900'



Gnd speed-Kts	70	90	100	120	140	160	
Descent Angle	3.00°	372	478	531	637	743	849
MAP at RW34 or FAF to MAP	5.0	4:17	3:20	3:00	2:30	2:09	1:53

STRAIGHT-IN LANDING RWY 34				CIRCLE-TO-LAND			
LNAV							
MDA(H) 1600' (376')							
ALS out				Max Kts.	MDA(H)	VIS	ALS out
				100	1640' (416')	1600m	2000m
				135	1720' (496')		
				180	1820' (596')	2400m	2800m
				205	1920' (696')	3600m	4000m

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

PANS OPS

CHANGES: Missed approach, bearings.

SANTA CRUZ, BOLIVIA
VOR Y Rwy 16


PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE


SLVR/VVI
VIRU VIRU INTL

16 AUG 13 (23-2)


SANTA CRUZ, BOLIVIA
VOR Z Rwy 16

BRIEFING STRIP™

VIRU VIRU Approach 119.7		VIRU VIRU Tower 118.6		Ground 121.9	
VOR VIR 113.8	Final Apch Crs 158°	Minimum Alt D5.1 3000' (1780')	MDA(H) 1610' (390')	Apt Elev 1224' Rwy 16 1220'	
MISSED APCH: Climb to 4000' direct VIR VOR, then direct to ENTIR/D10.0 VIR VOR, enter holding and request instructions from ATC.					
Alt Set: hPa 1. DME required.		Rwy Elev: 44 hPa	Trans level: By ATC		
			Trans alt: 5000'		MSA VIR VOR



DIST to MAP	4.4	3.0	2.0	1.0
ALTITUDE	3000'	2560'	2250'	1930'



Gnd speed-Kts	70	90	100	120	140	160	SALS PAPI 4000' ↑ D→ VIR 113.8
Descent angle	[2.98°]	369	474	527	633	738	
MAP at D0.7 or FAF to MAP	4.4	3:46	2:56	2:38	2:12	1:53	

STRAIGHT-IN LANDING RWY16				CIRCLE-TO-LAND			
MDA(H) 1610' (390')							
ALS out				Max Kts			
A				100	1640' (416') -2000m		
B	1600m		2000m	135	1720' (496') -2000m		
C				180	1820' (596') -2800m		
D	2000m		2400m	205	1920' (696') -4000m		

CHANGES: Procedure.


PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE


SLVR/VVI
VIRU VIRU INTL

1 JUN 18 **23-3**


SANTA CRUZ, BOLIVIA
VOR T Rwy 34

BRIEFING STRIP™

VIRU VIRU Approach 119.7		VIRU VIRU Tower 118.6		Ground 121.9	
VOR VIR 113.8	Final Apch Crs 339°	Minimum Alt D7.7 3000' (1776')	MDA(H) 1600' (376')	Apt Elev 1224' Rwy 1224'	
MISSED APCH: Climb to 4000' heading 339° to VIR VOR, RIGHT turn direct to GUTOG/D15.0 VIR VOR, enter hold, 189° inbound, LEFT turns, and request instructions from ATC.					
Alt Set: hPa		Rwy Elev: 44 hPa	Trans level: By ATC		
1. DME required.					Trans alt: 5000'
MSA VIR VOR					



DIST to THR	1.0	2.0	3.0	5.0	5.4
ALTITUDE	1600'	1906'	2222'	2854'	3000'



Gnd speed-Kts	70	90	100	120	140	160	HIALS PAPI	4000' ↑	339° hdg	VIR 113.8
Descent angle 3.00°	369	478	531	637	743	849				
MAP at D3.3 or FAF to MAP 4.4	3:46	2:56	2:38	2:12	1:53	1:39				

STRAIGHT-IN LANDING RWY34				CIRCLE-TO-LAND			
MDA(H) 1600' (376')							
ALS out				Max Kts			
A				100	1650' (426') -2000m		
B	1600m			135	1720' (496') -2000m		
C				180	1820' (596') -2800m		
D	2000m			205	1920' (696') -4000m		

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE


CHANGES: MSA flight level, recommended altitudes.

SLVR/VVI
VIRU VIRU INTL


1 JUN 18 (23-4)

SANTA CRUZ, BOLIVIA
VOR S Rwy 34


BRIEFING STRIP™

VIRU VIRU Approach 119.7		VIRU VIRU Tower 118.6		Ground 121.9	
VOR VIR 113.8	Final Apch Crs 339°	Minimum Alt D7.7 3000' (1776')	MDA(H) 1600' (376')	Apt Elev 1224' Rwy 1224'	
MISSED APCH: Climb to 4000' heading 339° to VIR VOR, RIGHT turn direct to GUTOG/D15.0 VIR VOR, enter hold, 189° inbound, LEFT turns, and request instructions from ATC.					
Alt Set: hPa		Rwy Elev: 44 hPa	Trans level: By ATC		
1. DME required.					

MSA VIR VOR



DIST to THR	1.0	2.0	3.0	5.0	5.4
ALTITUDE	1600'	1906'	2222'	2854'	3000'



Gnd speed-Kts	70	90	100	120	140	160		4000'	339° hdg	VIR 113.8
Descent angle	3.00°	369	478	531	637	743				
MAP at D3.3 or										
FAF to MAP	4.4	3:46	2:56	2:38	2:12	1:53				

STRAIGHT-IN LANDING RWY34					CIRCLE-TO-LAND				
MDA(H) 1600' (376')									
ALS out					Max Kts				
A					100	1650' (426') -2000m			
B	1600m		2000m		135	1720' (496') -2000m			
C					180	1820' (596') -2800m			
D	2000m		2400m		205	1920' (696') -4000m			


PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

CHANGES: MSA flight level, recommended altitudes.

SLYA/BYC
Apt Elev 2121'
S21 57.0 W063 39.3

28 JUL 17 10-9

YACUIBA, BOLIVIA
YACUIBA



ADDITIONAL RUNWAY INFORMATION

RWY		USABLE LENGTHS			WIDTH
		Threshold	Landing Beyond	Glide Slope	
03					118'
21					36m

TAKE-OFF	
All Rwys	
1 & 2 Eng	1600m
3 & 4 Eng	800m

CHANGES: Take-off minimums.

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE

SLYA/BYC
YACUIBA

28 AUG 15 (12-1)

MISSED APCH CLIMB GRADIENT MIM 4.4% YACUIBA, BOLIVIA
CAT A, B & C RNAV (GNSS) Z Rwy 21

*YACUIBA Tower 118.3


RNAV

Final
Apch Crs
210°

Minimum Alt
YA463
3800' (1679')

LNAV
MDA(H)
2830' (709')


Apt Elev 2121'
Rwy 2121'




MSA ARP

MISSED APCH: Turn **LEFT** heading **093°** direct **GIMTI**, climb to **6000'**, 4.4% climb gradient, and hold. Request ATC instructions.

Alt Set: hPa Rwy Elev: 75 hPa Trans level: By ATC Trans alt 16000'
1. **GNSS required.** 2. Max IAS 160 Kts. 3. La Paz/Cordoba FIR boundary located 3 NM South of RW21.



DIST to THR	2.1	3.0	4.0	5.0
ALTITUDE	2830'	3160'	3480'	3800'



Gnd speed-Kts	70	90	100	120	140	160	6000' LT	093° hdg		GIMTI
Descent Angle 3.00°	372	478	531	637	743	849				
MAP at RW21										

STRAIGHT-IN LANDING RWY21

Missed Apch Climb Gradient Mim 4.4%

LNAV


MDA(H) **2830'** (709')

CIRCLE-TO-LAND

Missed Apch Climb

Gradient Mim 4.4%

NO CIRCLING



A		Max Kts.	
B	1600m	100	3000' (879') - 2800m
C	2000m	135	3100' (979') - 3700m
D	NOT APPLICABLE	180	NOT APPLICABLE

CHANGES: Transition altitude, minimums format.

PARA USO EN AVIACIÓN VIRTUAL ÚNICAMENTE